



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
DIGGER DERRICK

DC SERIES

The Altec DC Series derrick offers fully hydraulic controls with similar capacities as the DM Series derrick. The DC Series full pressure system offers familiarity and practicality that many in the industry have used for decades. Popular T-Handle controller and boom side entry riding seat options and integrated safety features make this derrick a staple of the Electric Utility Industry.

FEATURES

- Multi-Lever Control Station Riding Seat
- Five Function Hydraulic Overload Protection System (HOP)
- Fiberglass Boom Tip and Transferable Steel Boom Flares
- Insulating Fiberglass Third Stage, Rated to 46kV and Below
- Hydraulic Side Load Protection
- 15,000 lb Worm Gear Turntable Winch with Rope Guides
- Hydraulic Tilting Pole Guides with Interlock
- 12,000 ft-lbs Digger Motor, Two Speed Mechanical Shift
- Hydraulic Auger Release
- Boom and Auger Stow Protection

OPTIONS

- T-Handle Controller
- Boom Side Entry Riding Seat
- Compact Riding Seat for Dual Pole Racks
- Below Rotation Control Stations
- Boom Tip Winch
- Integrated Multi-Lever Upper Controls
- Pole Guide Tong Protectors
- Single or Dual Platform(s)

Recommended equipment and additional accessories, available through Altec Supply, includes the AXIS Service Interface Kit, fall protection equipment, platform liner, wheel chocks and outrigger pads.

CONFIGURATIONS

		DC45	DC47
SPECIFICATIONS	Maximum Lift Capacity	28,040 lb (12,719 kg)	25,085 lb (11,378 kg)
	Maximum Capacity at 10 ft Radius (Without Options)	12,940 lb (5,869 kg)	12,430 lb (5,638 kg)
	Maximum Sheave Height* (Both Booms Extended)	44.4 ft (13.5 m)	46.4 ft (14.2 m)
	Reach from Centerline of Rotation	35.3 ft (10.8 m)	37.3 ft (11.4 m)
	Dig radius from Centerline of Rotation		
	Minimum	16.0 ft (4.9 m)	18.0 ft (5.5 m)
	Maximum	24.8 ft (7.6 m)	26.8 ft (8.2 m)
	Boom Articulation	-20° to +80°	
	Rotation	Continuous	
	Travel Height, approximate*	11.6 ft (3.5 m)	
*Based on chassis frame height of 40 inches (1016 mm)			



T-HANDLE CONTROLS



OPTIONAL UPPER CONTROLS



OPTIONAL SINGLE PLATFORM



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission. © 2021 Altec Inc. All Rights Reserved. AIOSDCSERIES-0321-v2



NEW EQUIPMENT SALES | 800.958.2555 | SALES@ALTEC.COM | ALTEC.COM

Courtesy of CraneMarket.com