

CORMACH WALLBOARD CRANE SPECIFICATIONS

MODEL	30000 WB-45	30000 WB-55	30000 WB-65	50000 WB-95
Ft/lb rating	279,250	269,120	258,270	464,663
Horizontal reach & capacity	44'2" – 4500 lbs	54' – 3040 lbs	65'1" – 1850 lbs	95'2" - 1322 lbs
Vertical reach & capacity	57' - 7600 lbs	67' – 5130 lbs	77' - 5250 lbs	106'6" - 5000 lbs
Lifting capacity	Max. 7600 lbs	Max. 7410 lbs	Max. 6350 lbs	Max. 8333lbs
	25' - 7600 lbs	25' – 7410 lbs	25' - 6350 lbs	25" - 6130 lbs
	35' - 5850 lbs	35' – 5150 lbs	35' - 4150 lbs	35" - 6130 lbs
	44' - 4500 lbs	45' – 3800 lbs	45' - 2980 lbs	45' - 4800 lbs
		54' – 3040 lbs	55' - 2270 lbs	55" - 3350 lbs
			65' - 1850 lbs	65' - 2150 lbs
				75" - 1800 lbs
				95' - 1322 lbs
Hydraulic ext.	2 (18'5")	3 (28')	4 (38'6")	3 (40'8") + 4(27'5")
Rotation	CONTINUOUS	CONTINUOUS	CONTINUOUS	CONTINUOUS
Rotation type	RING & GEAR	RING & GEAR	RING & GEAR	RING & GEAR
Controls	Top Seat	Top Seat	Top Seat	Top Seat
Valve type	Danfoss	Danfoss	Danfoss	Danfoss
Radio remotes	Optional	Optional	Optional	Optional
Operating pressure	4120 psi	4120 psi	4120 psi	4460 psi
Pump	Variable flow 26 g.p.m.	Variable flow 26 g.p.m.	Variable flow 26 g.p.m.	Variable flow 26 g.p.m.
Reservoir capacity	66 gallons	66 gallons	66 gallons	66 gallons
Oil cooler	Optional	Optional	Optional	Optional
Central grease system	Standard	Standard	Standard	Standard
Load limit device	Standard	Standard'	Standard	Standard
Outrigger span	25'	25'	25'	25'
Auxiliary outriggers	Optional	Optional	Optional	Standard – 19ft. span
Outrigger pads	Standard	Standard	Standard	Standard
Mount space (Crane only)	44"	44"	44"	44"
Operator platform	Standard	Standard	Standard	Standard
Crane weight	10270 lbs	10,870 lbs	11,510 lbs	14,130 lbs

2/2011