



E211i

THE ULTIMATE IN VERSATILITY— 3 MACHINES IN ONE

1. 190' material handling aerial work platform features a large 40" X 72", easy install/detach, 1200 lb capacity platform with curbside gated entrance. The platform will rotate 85° to each side and includes a 1,500 lb stowable, rotating material handling jib winch with nylon rope.
2. Add a 21' high-voltage insulated 500KV rated jib that is articulated to the actuator with a 36" X 72", 750 lb capacity, aluminum yoke-style, gravity-leveling platform and you have a machine that is ready for live line work.
3. A 21' steel jib can be used in lieu of Category A fiberglass jib, and it becomes a 211', 750 lb capacity aerial work platform with a steel yoke-style, gravity leveling, 36" X 72 platform. The jib is mounted to Helac rotational actuator which provides hyper and hypo elevation for flexibility in your construction activities.



BUILT FOR YOU

We know that every job is different and requires unique solutions to get the job done right. Starting with a wide range of optional equipment, Elliott's distributors and engineers will work with you to build exactly what you need to do your job, your way.



THE ELLIOTT E211i ALSO FEATURES:

- 360° continuous rotation
- EZ Crib Outriggers which provide 26' spread and an extended vertical stroke to reduce the amount of cribbing required on uneven terrain
- Can Bus controls with automotive relay modules to simplify wiring. These SMARTControls feature precise, proportional movement, an information screen and self-diagnostics
- Quick Connect hydraulic tool circuits (7 GPM) that can simultaneously operate two tools in the platform (no need for a hydraulic power unit in the platform which diminishes platform capacity)
- Hirschman Q-Scale system which monitors the unit in all jib/platform configurations
- Radio remote controls which provide a screen for viewing system information
- A ride-around, premium seated operator control console includes a 12-volt outlet and cup holder
- Steel bed wings treated with a military-grade non-skid coating
- A lifetime structural warranty and 1-year service warranty

The Elliott E211i will mount on a commercial, twin-steer tridem with a travel length of 48' (56' with platform attached). Travel height does not exceed 13'6" with platform attached.