



TAG-A-LONG, 30 TON
30TA120214



TAG-A-LONG, 30 TON
3 AXLE, MAXIMUM PAYLOAD 60,000 LBS



TAG-A-LONG, 30 TON

Features & Benefits



Ramps



Adjustable with spring assist and safety bar.

Hydraulic Ramps



Hydraulic ramp upgrade available for easier use.

Axles



25,000 lbs capacity axles.

Wheel Options



All Globe trailers come with standard HUB piloted disc wheels. Wheels are also available in all Aluminum or Outer Aluminum.

Decking Options



Oak: Standard.
Apitong: Best strength to weight ratios of natural woods.
Rumber: Composite which is impervious to fluids, mud, oil and UV rays.

Heavy Duty Pintle Eye



3" Pintle eye, with 4 adjustable height positions, with 2 heavy duty safety chains and grab hooks.

Tie Downs



D-rings on each side of the deck make it easier to secure loads to the trailer.

Landing Gear



2 speed Landing Gear, allows for 160,000 lbs static load.

Suspension



Heavy Duty tri-axle suspension.

TAG-A-LONG, 30 TON

Features & Benefits



Lighting System



All Lighting is LED and mounted in rubber grommets to DOT standards.

Tool Box



Lockable tool box with anti theft provisions available.

Color Coded Hoses



Color coded air hoses allow for easy trouble shooting and maintenance.

High Quality Steel



Constructed of high quality steel allowing for longer trailer life and greater durability. Main beams constructed using 14" steel beams.

Color Options



Globe Trailers can powder coat to the color of your choice.


STEMCO Wheel Warranty



5 year wheel end warranty. Guardian wheel seals, Pro-Torq spindle nuts and Sentinel hub caps.



All Globe Trailers are 100% powder coat finished. The entire process takes place at Globe's manufacturing facility. This eliminates the possibility of contamination occurring in transit between process phases. The process starts with sandblasting the trailer to near white, preheating the trailer steel in a dedicated, gas fired oven to optimum bonding temperature and applying an electrostatically charged zinc rich primer. The trailer then goes back in the oven to allow the primer to bond. After the primer has bonded, a top coat chosen from one of Globe Trailers' 188 color options is applied before once more going back in the oven to cure. The result is a durable, easily cleaned finish that protects the trailer from corrosion and ensures a long service life.



Overall Length	Overall Width	Deck Length	Deck Height	Beavertail Length	Drawbar Length
36' 8" (440")	8' 6" (102")	24' TA	34"	60"	62.50"

Frame	
Main Beam	14 x 6.75 @ 43#
Main Beam Centers	39"
Side Rails	10" Channel
Crossmembers	4" IB
Spacing	12"
Bumper	10" Channel
Header	8" Channel
# of D-Rings	6 Each Side
Drawbar	
Tool Box	Lockable w/ Steel Grating
Hitch Type	3" Pintle Hitch
Safety Chains with Hooks	
Beavertail & Ramps	
Beavertail 60"	
Rear Ramps 24 x 60	
Spring Assist	
Cleated	
Electrical	
Lights	LED S/T/T Only
Connector	7 Way Connector
Decking/Flooring	
Main Decking	1.75", Oak Full Width
Beavertail Flooring	Steel Covered S-Plate w/Grousers

Axles, Suspension, & Running Gear	
# of Axles	3
Axle Spacing	49"
Axle Capacity	25,000 lbs
Axle Track	71 1/2"
Brakes	12 1/4" x 7 1/2" - 25K
ABS	2S1M
Axle 1	Fixed Type 30/30 Non-ABS
Axle 2	Fixed Type 30/30 ABS
Axle 3	Fixed Type 30/30 Non-ABS
Suspension	Spring Ride 25K
Landing Gear	Dual 2-Speed 50K Drop Leg Jacks
Tires & Rims	
Tires	235/75R x 17.5 "H"
Rims	6.75 X 17.5 Hub Piloted Steel
Finish	
Sand Blasted and Powder Coat (Color of Choice)	
Mud Flaps & Reflective Tape	
Dealer:	