
GROVE® GRI540

Capacity: 40 USt (40 t) **Main boom:** 102 ft (31 m)

Maximum boom extension: 26 ft - 45 ft (7,9 m - 13,7 m)

Maximum tip height: 154 ft (46,9 m)



GRT540

- The same Crane Control System you've come to expect on Grove Rough Terrain cranes, now on a single 12 inch (30.5 cm) touchscreen display
- Simple, intuitive functionality for quick set-up and enhanced operation
- New driving mode includes steering indication, fore and aft as well as side to side slope indication, travel speed and more
- Asymmetrical outrigger positioning systems that allows for maximum accessibility on any jobsite
- Provides increased capacities vs. standard 360° load charts for increased utilization & lower project costs
- Panorama view via the CCS display provides real time visual feedback to the operator with built in function stops when limits reached

- Enhanced diagnostics and monitoring systems for easy serviceability
- · On-board monitoring of all hydraulic pressures from the cab
- · On-board calibration of sensors via use of day code
- Telematics system that provides easy access to your complete fleet in real time
- View live crane activity, configuration, RCL data, GPS, faults, hours and more
- Create reports based around maintenance programs, crane utilization, crane performance, software status, maintenance alerts, etc.
- Manage fleets with automatic maintenance alerts, servicerelated observations, and parts ordering before dispatch



