







CARGAS / LOADS / CHARGES / НАГРУЗКИ / YÜKLER / الأحمال **J215**

ST-SR (kg)		Cargas máximas / Maximum loads / Charges maximales / Максимальные нагрузки / Maksimum yük / أقصى حمولة SR - 5.000 kg							
 [m]	5000 kg @ ... (m)	Alcance del gancho [m] / Hook reach [m] / Portée du crochet (m) / Радиус действия крюка (m) / Kancanın yüksekliği (m) / مدى الخطاف							
		30	35	40	45	50	55	60	65
65 m	37,8	5000	5000	4670	4045	3540	3130	2790	2500
60 m	39,9 m	5000	5000	4995	4330	3795	3360	3000	—
55 m	43,9 m	5000	5000	5000	4865	4280	3800	—	—
50 m	46,7 m	5000	5000	5000	5000	4600	—	—	—
45 m	45,0 m	5000	5000	5000	5000	—	—	—	—
40 m	40,0 m	5000	5000	5000	—	—	—	—	—
35 m	35,0 m	5000	5000	—	—	—	—	—	—
30 m	30,0 m	5000	—	—	—	—	—	—	—

 ST- DR (kg)		Cargas máximas / Maximum loads / Charges maximales / Максимальные нагрузки / Maksimum yük / أقصى حمولة DR - 10.000 kg								
 [m]	10000 kg @ ... (m)	Alcance del gancho [m] / Hook reach [m] / Portée du crochet (m) / Радиус действия крюка (m) / Kancanın yüksekliği (m) / مدى الخطاف								
		25	30	35	40	45	50	55	60	65
65 m	20,5	7970	6435	5335	4515	3875	3360	2945	2595	2300
60 m	21,6 m	8480	6855	5695	4825	4150	3610	3170	2800	—
55 m	23,7 m	9425	7645	6375	5420	4680	4085	3600	—	—
50 m	25,1 m	10000	8170	6825	5815	5030	4400	—	—	—
45 m	25,4 m	10000	8275	6915	5895	5100	—	—	—	—
40 m	25,8 m	10000	8420	7035	6000	—	—	—	—	—
35 m	26,0 m	10000	8490	7100	—	—	—	—	—	—
30 m	26,0 m	10000	8500	—	—	—	—	—	—	—

CARACTERISTICAS DE MECANISMOS / MECHANISMS FEATURES / CARACTÉRISTIQUES DES MÉCANISMES / ХАРАКТЕРИСТИКИ МЕХАНИЗМОВ / MEKANİZMALARIN ÖZELLİKLERİ / الخصائص الآلية **J215**












*opcional *optional *en option *опция *opsiyonel *اختياري							
	*EC3350VF 24,3 kW	EC4860 35,3 kW	*EC6080VF 44,1 kW	TG2020VF 2x7,3 kW	OG1507VF 2x5,5 kW	TC590VF 4 kW	TH2006 15 kW
 t m/min		2,5 5 5 60 30 7		0...20 m/min	0...0,8 r/min sl/min	5 t 0...90 m/min 10 t 0...45 m/min	0,6 m/min
 t m/min		5 10 10 30 15 3,5		 400V 50Hz 480V 60Hz	P _{TOTAL} (EC3350VF+ OG1507VF + TC590VF) = 39,3 kW P _{TOTAL} (EC4860+ OG1507VF + TC590VF) = 50,3 kW P _{TOTAL} (EC6080VF+ OG1507VF + TC590VF) = 59,1 kW EC4860 kW +20% m/min +20%		
 H ≤	SR 324 m DR 162 m	H ≤	SR 534 m DR 267 m		 kg		



Fecha / Date: 01/09/2017

Reservado el derecho a modificaciones sin previo aviso. Declinamos toda responsabilidad derivada de la información proporcionada / Subject to modification, without previous warning. This information is supplied without liability / L'entreprise se réserve le droit de procéder à des modifications sans préavis. Nous déclinons toute responsabilité quant aux informations fournies / Мы оставляем за собой право на внесение изменений без предварительного уведомления. Мы снимаем с себя любую ответственность в отношении предоставленной информации / Önceden bildirilmeksizin değiştirilme hakkı saklıdır. Verilen bilgiler için hiçbir sorumluluk kabul etmemektediriz / حقوق التغيير محفوظة دون إشعار مسبق. دون أدنى مسؤولية عن المعلومات المقدمة

 **FEM 1001**

LISTA DE EMBARQUE / PACKING LIST / LISTE DE COLISAGE / СПИСОК ПОСТАВКИ / ÇEKİ LİSTESİ / قائمة التحميل				J215			
DENOMINACIÓN / DENOMINATION / DÉSIGNATION / НАЗВАНИЕ / AÇIKLAMA / اسم				L [m]	A [m]	H [m]	P / W [kg]
Torre inferior / Lower tower / Tour inférieure / Нижняя башня Alt kule / البرج السفلي		T1-6-150		6,175	2,190	2,190	3.535
Torre / Tower / Tour Башня / Kule / برج		T6-150 TD6-150 T3-150 T12-150		6,175 6,175 3,265 12,000	1,870 1,870 1,870 1,870	1,870 1,870 1,870 1,870	2.760 2.930 1.550 5.180
Torre asiento pista + base punta de torre + orientación Slewing table + tower head base + slewing mechanism Tour pivot + base du porte-flèche + mécanisme d'orientation Сиденье площадки + основание верхней секции башни + поворотный механизм Göbek +kule kafa bölümü tabanı+mekanizma برج وحدة الدوارن + قاعدة رأس البرج + آلية الدوران				4,660	2,350	2,275	5570
Punta de torre / Tower head / Porte-flèche верхняя секция башни / kulinin kafa bölümü / رأس البرج				7,680	1,200	1,650	2675
Conjunto asiento pista, punta de torre, orientación Slewing table assembl +, tower head + slewing Groupe pivot + porte-flèche + mécanisme d'orientation Сиденье площадки + верхняя секция башни + поворотный механизм Göbek +kulinin kafa bölümü+mekanizma مجموعة وحدة الدوارن + رأس البرج + آلية الدوران				11,490	2,920	2,710	8490
Tramo de pluma Jib section Tronçon de flèche Секция стрелы Bot bölümü أجزاء الذراع		P17-23N P17-24N P17-25N P17-26N P17-27N P17-30N P17-29N P17-19N		8,800 10,166 10,170 10,166 10,166 10,166 5,276 2,222	1,75 1,6 1,6 1,6 1,6 1,6 1,6 1,74	2,015 1,905 2,005 1,970 1,970 1,905 1,885 2,195	1520 1660 1635 1425 1355 1300 505 340
Polipasto / Hook assembly / Palan / Полуснаст / Kanca takımı / بكرة			SR/ DR 	1,410	0,550	0,920	410
Tirante sostén pluma / Jib support tie / Tirant de fleche / Растяжка поддержки стрелы / Kol destek bağları / مشد دعامة الذراع		2x 2x 1x		6,170 6,170 4,965	0,36 0,36 0,36	0,586 0,586 0,245	1505 1421 730
Carro / Trolley / Chariot / Грузовая тележка / Şaryo / عربة		SR/DR		1,790	2,415	1,575	450
Contrapluma con plataformas / Counterjib with platforms Contre-flèche avec plateformes / Противовесная консоль с платформами / Platformlu kuyruk / الذراع المقابل مع المنصة				12,128	2,984	0,58	2540
Prolongación contrapluma con plataforma / Counterjib extension with platform Prolongement contre-flèche avec plateforme / Удлинение противовесной консоли с платформой / Kuyruk platformla uzatılması / امتداد الذراع المعاكس مع الممرات				4,295	1,75	0,336	620
Plataforma y cabina / Platform and cabin / Plateforme et cabine Платформа и кабина / Platform ve kabin / منصة وكابينة				3,760	2,050	2,400	1280
Soporte y elevación (sin cable) / Support and hoisting (without rope) / Support et levage (sans câble) / Опора и подъем (без троса) / Destek ve vinç kulesi (kabloşuz) / دعم ورفع (بدون كابل)		EC3350VF EC4860 EC6080VF		3,245 3,245 3,245	1,675 1,675 1,675	1,557 1,905 1,940	2500 2800 2830
Estructura torre de montaje / Jacking cage structure / Structure de tour de montage / Структура монтажной башни / Kaldırma kafesi yapısı / هيكل برج التركيب		TM6-150		10,320	2,420	2,310	3500
Lastre / Ballast / Lest / Балласт / Alt ağırlik taşları / ثقل				3,8	0,58	1,5	6000

LASTRES INFERIORES / LOWER BALLASTS / LESTS INFÉRIEURS / НИЖНИЙ БАЛЛАСТ / BALAST / ثقل				J215			
BNI 6-150		H (m)	29,2	40,8	55,1		
		P (t)	48	60	84		

H: Altura bajo gancho / Height under hook / Hauteur maximale sous crochet Высота под крюком / Kanca altı yüksekliği / الارتفاع أسفل الخطاف
 Para alturas intermedias tomar el lastre correspondiente a la altura superior / For intermediate heights take the ballast corresponding to the higher height / Pour les hauteurs intermédiaires, opter pour le
 lest correspondant à la hauteur immédiatement supérieure / Для промежуточных высот возьмите балласт, соответствующий большей высоте / Orta yükseklikler için daha üst bir yüksekliğe
 karşılık gelen ağırlığı alınız. / لارتفاعات البينية يرجى استخدام الثقل العائد للارتفاع الأعلى /



Fecha / Date: 01/09/2017

Reservado el derecho a modificaciones sin previo aviso. Declinamos toda responsabilidad derivada de la información proporcionada / Subject to modification, without previous warning. This information is supplied without liability /
 L'entreprise se réserve le droit de procéder à des modifications sans préavis. Nous déclinons toute responsabilité quant aux informations fournies / Мы оставляем за собой право на внесение изменений без предварительного
 уведомления. Мы снимаем с себя любую ответственность в отношении предоставленной информации / Önceden bildirilmeksizin değiştirilme hakkı saklıdır. Verilen bilgiler için hiçbir sorumluluk kabul etmemekteyiz
 حقوق التغيير محفوظة دون إشعار مسبق. دون أدنى مسؤولية عن المعلومات المقدمة

FEM 1001

