KOMATSU® WH714

LIFTING HEIGHT

14.100 mm

LIFTING CAPACITY 4.000 kg

OPERATING WEIGHT 10.885 kg

WH 714

WH714



WH714



SPECIFICATIONS



ENGINE

The engine has been developed in compliance with the strictest European standards (EEC 97/68 - STAGE 2) on the reduction of exhaust emissions.

Model	Komatsu S4D104E-1
Туре	4-cycle water-cooled diesel engine
Displacement	4,5 ℓ
No. of cylinders	4
	turbo
Rated nower:	
SAE J 1349	74 (99,2) @ 2.300 kW (HP)/rpm
EEC 80/1269	74 (99,2) @ 2.300 kW (HP)/rpm
	398 @ 1400 Nm/rpm



OPERATING WEIGHT

Standard machine operating weight......10.885 kg



BRAKES

Service brakes servo-assisted with 2 independent lines acting on both axles.

Service brakes typeoil immersed multi-disk Parking brakes typeacting on service brakes



TYRES

Standard14,00 - 24



STEERING

4 drive and steering wheels with 3 steering modes (2 wheel, circle and crab steering).

Turning ra	adius over	tires	3.720 mm
Turning ra	adius over	forks	5.330 mm



TRANSMISSION

TypeFull Power Shift with EGS control system Max speed38 km/h



HYDRAULIC SYSTEM

Type	Close Load Sensing System CLSS
Pump	Variable displacement, axial pistons
Max operating pressure	
	142 <i>e</i> /min



ELECTRIC SYSTEM

Voltage	12 V
Battery	
Alternator	
Starter	3 kW



REFILLS

Diesel tank	130 ℓ
Hydraulic oil tank	125 ℓ




CONTROLS

PPC joystick (Proportional Servo-Control)



OPERATING PERFORMANCES

Max lifting height	14.100 mm
Max lifting capacity	
Capacity at max height	4.000 kg
Max forward reach	9.600 mm
Capacity at max forward reach	1.300 kg





Komatsu Utility Europe

Head Office via Atheste 4 35042 Este (Padova) - Italy Tel. +39 0429 616111 Fax +39 0429 601000 www.komatsueurope.com utility@komatsu.it





