

PG Series | LK24P22

CONSTRUCTION INDUSTRY



Courtesy of CraneMarket

LK24P22 Specifications

Capacity @ 24" LC	24,000 Lbs. (10,885 kg)	Drive	2 Wheel, Front
Length (less forks)	260" (6605 mm)	Steering	2 Wheel, Rear
Width	97" (2465 mm)	Lift Height	168" (4265 mm)
Height - overhead guard	129" (3275 mm)	Carriage Width	60" (1525 mm)
Wheelbase	110" (2795 mm)	Tilt Forward	3 Deg.
Turning Radius	173" (4395 mm)	Tilt Rearward	10 Deg.
Ground Clearance	11" (280 mm)	Fork Length	48" (1220 mm)
Weight	33,000 Lbs. (14,970 kg)	Electrical	12V DC Negative Ground

Engine	Perkins Tier 3, 4-cylinder 141 hp (105 kW) Turbo Diesel
Transmission	2-Speed Powershuttle
Axle - drive	Internal Reduction with Planetary Hubs
Axle - steer	High Steer Angle with Oscillating Mount
Service Brakes - drive / steer	Drum, Hydraulic / Disc, Hydraulic
Parking Brake	Drum on Transmission Output, Manual
Tires - all	Non-directional Lug, 9.00 x 20
Capacities - fuel / hydraulic	85 U.S. gallons (303 L)

Liftking's LK24P22 - a modern day Workhorse.

Designed to military specifications then adapted for commercial use, the LK24P22 is unique in many ways.

- One of the main design criteria's was to maximize productive uptime by eliminating all non-critical components, thereby reducing potential points of failure while simplifying maintenance and repairs.
- Run time between fuel fill-ups is extended by utilizing an extra-capacity fuel tank while the equally large hydraulic tank allows greater intervals between hydraulic system servicing.
- The six engine compartment maintenance doors allow unfettered access to vital mechanical components while all routine maintenance points are strategically located for quick and easy daily checks.
- The fully sealed and integrated steel column and instrument clusters greatly minimizes in-cab wiring and allows all functions to be controlled and monitored from a centralized location.

These are just some of the features that sets the LK24P22 apart from the competition.

When considering what the LK24P22 is capable of in the military field, imagine what it can do at your jobsite.



STANDARD EQUIPMENT:

Heavy Duty Clearview Roller Mast with Dual Chains

- Hydraulic Fork Positioner
- FOPS Operator Compartment
- Hydraulic Brakes
- Power Steering
- Soft-shift Powershift Transmission
- Tier 3 Turbo Diesel Engine
- Headlights and tail lights
- Wide grip handrails
- Ion-nitride cylinder rods
- Extra wide steps
- Asbestor-free brake linkings
- Trailer hitch
- Electric horn and automatic Backup alarm
- Tilt steering column with anti-restart ignition and neutral safety interlock
- Adjustable seat
- Extra thick fenders for maximum safety and durability
- Engine oil pressure gauge, fuel gauge, hour meter, and warning lights
- Operator, maintenance and illustrated parts manuals included
- 1 Year / 2000 hours limited warranty (2 year engine warranty)

OPTIONAL EQUIPMENT:

Various mast/carriage/fork types and sizes

- Various engines
- Lockable engine hood, fuel and hydraulic caps
- Air Pre-cleaner
- Fluid sampling ports
- High durability powder coat paint
- Adjustable height strobe light and additional lighting
- DS Safety rating
- Tinted Windows
- Sun visor
- Power Assisted Brakes
- Deadman seat
- Safety-Start Seatbelt
- Heated Mirrors
- Cold Weather Package
- 12V Outlet
- Radio
- Cup holders
- Weigh scale
- Enclosed all weather operator compartment with HD heater, sliding windows, wipers, lift-off doors
- ROPS Operator compartment
- Air Conditioning
- Air ride suspension seat with arm rests and retractable safety belt
- Foam filled tires
- Towing package
- Contact dealer for other options.



Manitex Liftking reserves the right to make changes in specifications shown, herein, and improvements, or discontinue manufacture at any time without notice or obligation. The information contained herein is general in nature and is not intended for specific application purposes.

7135 Islington Avenue, Woodbridge, Ontario. L4L 1V9
Tel: 905-265-3965 | Fax: 905-851-6396

www.manitexliftking.com

03/15