

# 85|RT

Rough Terrain Crane 85-ton | 80 mt

#### Bridging the full power gap between the medium and large class machines



85-ton | 80 mt Rough Terrain Crane

#### **Standard Features & Benefits**













- New Tie off anchors for fall protection
- Operator aids with kickout

Link-Belt

- Next generation operator's cab with 20° tilt
- Ergonomic ladders and grab handles
- Link-Belt Pulse 2.0 LMI
- V-CALC
- Full LED lighting package
- 3 on-board cameras
- Anti-skid textured paint

#### Transport weight of less than 105,000 lbs includes:

- Main & aux winches with wire rope & cable followers
- 35'-58' | 10.7-17.7 m 2-piece SmartFly stowed 19, 200 lbs | 8.7 m full counterweight package
- 60 ton | 55 m hook block 10 ton | 9 m hook ball
- Aux lifting sheave
- Full tank of fuel



## Latest, simple, one-man fly erection technology minimizes work-at-height!

- One man operation
- Swing around at 0°
- Minimal ladder climbs
- Control fly assist and boom hoist cylinder from the ground
- Pivot-point & boom head speed screws

#### **Centralized pressure** check and grease bank





Allows operator to check eight (8) pressures and grease four (4) different points from one centralized location on the upper frame. Boom foot pins, head machinery sheaves, and cab tilt cylinder are also greaseless

### Vision package See what you've been missing





#### Service and maintenance just got easier!

- REMOTE MOUNTED TRANSMISSION OIL. ENGINE OIL. AND FUEL FILTERS
- 24 VOLT ELECTRICAL SYSTEM
- **CENTRALIZED GREASE BANK AND PRESSURE CHECKS**
- **MULTIPLEXING CANBUS NETWORK**
- **GREASELESS FOUR-LINK SUSPENSION**
- **SERVICABLE PONTOONS**
- **SWING OUT ENGINE ACCESS DOORS**
- ADDED STORAGE BOX LOCATIONS



Link-Belt Cranes | Lexington, Kentucky www.linkbelt.com

® Link-Belt is a registered trademark. Copyright 2021. All rights reserved We reserve the right to change designs and specifications at any time Litho in U.S.A. 4130 11/21 #4591