




		fixing angles	static base 3.8m	static base 4.6m
jib length (m)		25.0-55.0	25.0-55.0	25.0-55.0
tower height	TM 13	48.2m	49.6m	49.6m
	TM 13v	54.2m	--	--

jib length & maximum load										
jib length		max. load		jib length						
m	rope	t	m	25	30	35	40	45	50	55
55		3.0	34.5	3.00	3.00	2.95	2.52	2.18	1.92	1.70
		6.0	18.6	4.34	3.53	2.96	2.53	2.19	1.92	1.70
50		3.0	38.4	3.00	3.00	3.00	2.88	2.50	2.20	
		6.0	20.8	4.90	4.00	3.36	2.88	2.50	2.20	
45		3.0	40.5	3.00	3.00	3.00	3.00	2.70		
		6.0	22.2	5.26	4.30	3.61	3.10	2.70		
40		3.0	40.0	3.00	3.00	3.00	3.00			
		6.0	22.8	5.42	4.43	3.73	3.20			
35		3.0	35.0	3.00	3.00	3.00				
		6.0	23.2	5.52	4.52	3.80				
30		3.0	30.0	3.00	3.00					
		6.0	23.5	5.62	4.60					
25		3.0	25.0	3.00						
		6.0	22.5	5.70						

Hoisting velocities 400-440V; 50-60Hz							
Hoist winch 30kW with frequency inverter							
	Load (t)	1.1	1.2	1.5	1.8	2.3	3.0
	v (m/min)	141	123	105	86	68	50
	Load (t)	2.2	2.4	3.0	3.6	4.6	6.0
	v (m/min)	70	61	52	43	34	25
Hoist drum capacity		400.0m					

Motor	3.0kW fi	2 x 3.0kW	2 x 5.0kW
t/v	0.0 - 80.0m/min	0.85 min ⁻¹	25.0 m/min
electrical power supply for crane top		hoist winch 30kW	48 kVA

version 03/13, subject to amendments



available with:



MTI-LUX S.A.

51, route de Wasserbillig
6686 Mertert
Luxemburg



00352 26 74 54 80



00352 26 74 54 83



info@mti-lux.com



www.mti-lux.com

