



# TM240 Series

## CRANE STANDARD FEATURES & OPTIONS

- **24Ton (21,7 tm) Capacity @ 5' (1,5 m) Radius**
- **Boom Options**
  - ❑ 6-Section 19' - 85' (5,8 – 26 m) Boom
  - ❑ Compact Self Aligning Formed Boom
  - ❑ Maximum Tip Height – 95' (29 m)
  - ❑ Internally Routed Anti-Two Block Cable
  - ❑ Maintenance Free Slider Pads
  - ❑ Grooved Drum with Negative Draft Angle Flanges
- **Hydraulics System**
  - ❑ Hydraulic Reservoir Capacity: 70 gal. (265 L)
  - ❑ Oil Cooler/Heat Exchange
  - ❑ Suction Strainer and Ball Valve
  - ❑ 3 Section Gear Pump
- **Outriggers**
  - ❑ Front Out and Down Outriggers 7' 5" – 19' 8" (2,1 - 6 m)
  - ❑ Rear H-Configuration Stabilizer 7'5" (2,25 m)
  - ❑ 3 position Outriggers. Full, Mid, and Retracted Capacities.
- **Control System**
  - ❑ Dual Operating Stations Equipped with Four Single-Lever Crane Controls
  - ❑ Individual Control Levers for Each Outrigger and Stabilizer
  - ❑ Burst of Speed, 2 Speed Winch
- **Safety Features**
  - ❑ Engine Start/Stop
  - ❑ Electronic Foot Throttle
  - ❑ Outrigger Monitor System
  - ❑ LMI with Audio and Visual Shutoff/Cutouts
  - ❑ Signal Horn
- **Options**
  - ❑ 360 Degree Work Area with Front Center Stabilizer
  - ❑ 4-Function Radio Remote Crane Control System
  - ❑ Tool Box Chassis Mount
  - ❑ 3-Section Vane Pump, SAE B Input
  - ❑ Load Blocks

