MANITOWOC ENGINEERING CO.
Division of The Manitowoc Company, Inc. Manitowoc. Wisconsin 54220

LIFTCRANE CAPACITIES

BOOM NO 22 WITH OPEN THROAT TOP
47 360 kg CRANE COUNTERWEIGHT
360 DEGREE RATING

Meets
AS1418.5
Table 9.4.2.1 (a)

Meets
ANSI B30.5
Requirements

4000 W

SERIAL NO 40544

LIFTING CAPACITIES: CAPACITIES FOR VARIOUS BOOM LENGTHS AND OPERATING RADII ARE FOR FREELY SUSPENDED LOADS, AND MAY BE BASED ON PERCENT OF TIPPING, STRENGTH OF STRUCTURAL COMPONENTS, OPERATING SPEEDS AND OTHER FACTORS. CAPACITIES ARE IN KILOGRAMS AND CORRESPOND TO AS1418.5 1995 TABLE 9.4.2.1(a). TEST LOADED ON CRAWLERS TO 1.5P + 0.1F. CAPACITIES BASED ON STRUCTURAL COMPETENCE ARE DENOTED BY AN ASTERISK (*).

UPPER BOOM POINT CAPACITY FOR LIFTCRANE SERVICE WITH SINGLE PART WHIP LINE OR COMBINATION OF TWO SINGLE PART LINES IS 12 840 kg. (9 070 Kg. WHEN REAR AUXILIARY DRUM IS USED). IN ALL CASES, UPPER HOOK POINT CAPACITIES CANNOT EXCEED THOSE LISTED FOR THE MAIN BOOM CAPACITY.

WEIGHT OF UPPER BOOM POINT, JIB, ALL LOAD BLOCKS, HOOKS, WEIGHT BALL, SLINGS, HOIST LINES, ETC., BENEATH BOOM AND J IB POINT SHEAVES, IS CONSIDERED PART OF THE MAIN BOOM LOAD. BOOM IS NOT TO BE LOWERED BEYOND RADII WHERE COMBINED WEIGHTS ARE GREATER THAN RATED CAPACITY. WHERE NO CAPACITY IS SHOWN, OPERATION IS NOT INTENDED OR APPROVED. CAPACITIES SHOWN ARE NOT TO BE EXCEEDED.

WARNING: WHEN TRAVELLING WITH LOAD (PICK & CARRY) TRAVEL SPEED IN EXCESS OF 0.4 m/s IS NOT PERMISSIBLE. WHEN TRAVELLING WITHOUT A LOAD TRAVEL SPEED IN EXCESS OF 0.4 m/s IS PERMISSIBLE.

OPERATING CONDITIONS: MACHINE TO OPERATE IN A LEVEL POSITION ON A FIRM UNIFORMLY SUPPORTING SURFACE WITH GANTRY UP. REFER TO BOOM RIGGING DWG. No. 48168 AND WIRE ROPE SPECIFICATION CHART NO. 6864-A. CRANE OPERATOR JUDGEMENT MUST BE USED TO ALLOW FOR DYNAMIC LOAD EFFECTS OF SWINGING, HOISTING OR LOWERING, TRAVEL, WIND CONDITIONS, AS WELL AS ADVERSE OPERATING CONDITIONS AND PHYSICAL MACHINE DEPRECIATION.

OPERATING RADIUS: OPERATING RADIUS IS THE HORIZONTAL DISTANCE FROM THE AXIS OF ROTATION TO THE CENTER OF VERTICAL HOIST LINE OR LOAD BLOCK. BOOM ANGLE IS THE ANGLE BETWEEN HORIZONTAL AND CENTERLINE OF BOOM BUTT AND INSERTS, AND IS AN INDICATION OF OPERATING RADIUS. IN ALL CASES, OPERATING RADIUS SHALL GOVERN CAPACITY. BOOM POINT ELEVATION IS VERTICAL DISTANCE FROM GROUND LEVEL TO CENTERLINE OF BOOM POINT SHAFT.

MACHINE EQUIPMENT: MACHINE EQUIPPED WITH 7 315 mm EXTENDIBLE CRAWLERS, 1 219 mm TREADS, 4 572 mm RETRACTABLE GANTRY, 12 PART BOOM HOIST REEVING, FOUR 35 mm BOOM PENDANTS, 1st COUNTERWEIGHT = 18,190 kg (17 690 Kg WITH COUNTERWEIGHT ASSEMBLY No. 48998, 2nd COUNTERWEIGHT = 16 240 kg, AND 3rd COUNTERWEIGHT = 12 930 Kg.

MAXIMUM BOOM AND JIB LENGTHS LIFTED UNASSISTED

OVER END OF BLOCKED CRAWLERS		OVER SIDE OF EXTENDED CRAWLERS		OVER SIDE OF RETRACTED CRAWLERS	
BOOM LGTH.	JIB NO. 123	BOOM LGTH.	JIB NO. 123	BOOM LGTH.	JIB NO. 123
67.1m	---	61.0m	---	57.9m	---
64.0m	---	57.9m	---	54.9m	---
61.0m	12.2m	54.9m	15.2m	51.8m	15.2m
57.9m	18.3m	51.8m	18.3m	48.8m	18.3m

LOAD BLOCK, HOOK AND WEIGHT BALL ON GROUND AT START. UPPER BOOM POINT CANNOT BE USED ON 67.1m BOOM.

DEDUCT FROM CAPACITIES WHEN UPPER BOOM POINT IS ATTACHED	
ONE SHEAVE POINT	540 kg
TWO SHEAVE POINT	680 kg

DEDUCT FROM CAPACITIES WHEN JIB IS ATTACHED	
JIB LGTH.	JIB NO. 123
9.1m	1 360 kg
12.2m	1 630 kg
15.2m	1 910 kg
18.3m	2 220 kg

JIB DEDUCTS INCLUDE JIB ADAPTOR.

CONSULT JIB CHART FOR JIB CAPACITIES.

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
21.3	70	4.5	80.6	23.2	158 700*	158 700*
		5.0	79.5	23.1	133 300	146 700*
		5.5	78.1	23.0	111 900	128 900*
		6.0	76.8	22.9	96 300	117 400*
		7.0	74.0	22.7	75 000	90 000
		8.0	71.2	22.4	61 300	72 600
		9.0	68.3	22.0	51 700	60 500
		10.0	65.4	21.6	44 500	51 800
		11.0	62.4	21.1	39 000	45 200
		12.0	59.3	20.5	34 700	40 000
		14.0	52.9	19.2	28 100	32 300
		16.0	45.8	17.5	23 600	27 000
		18.0	37.7	15.2	20 100	23 000
		20.0	27.7	12.1	17 500	20 000

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
24.4	80	4.9	81.1	26.3	139 800	141 000*
		5.0	80.8	26.2	133 600	140 200*
		5.5	79.6	26.2	111 800	128 300*
		6.0	78.4	26.1	96 100	116 900*
		7.0	76.0	25.8	74 800	89 900
		8.0	73.6	25.6	61 100	72 400
		9.0	71.1	25.2	51 400	60 300
		10.0	68.6	24.9	44 300	51 600
		11.0	66.1	24.5	38 800	45 000
		12.0	63.5	24.0	34 400	39 700
		14.0	58.1	22.9	27 900	32 100
		16.0	52.4	21.5	23 300	26 700
		18.0	46.2	19.8	19 900	22 700
		20.0	39.3	17.6	17 200	19 700
		22.0	31.1	14.8	15 100	17 300
		24.0	20.2	10.6	13 400	15 300

CHART No 62[illegible]

Courtesy of Crane Market

MANITOWOC ENGINEERING CO.
Division of The Manitowoc Company, Inc. Manitowoc. Wisconsin 54220

LIFTCRANE CAPACITIES

BOOM NO 22 WITH OPEN THROAT TOP
47 360 kg CRANE COUNTERWEIGHT
360 DEGREE RATING

Meets
AS1418.5
Table 9.4.2.1 (a)

Meets
ANSI B30.5
Requirements

4000 W

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
27.4	90	5.2	81.4	29.3	121 100*	121 100*
		5.5	80.8	29.2	111 700	121 000*
		6.0	79.7	29.2	96 000	115 800*
		7.0	77.6	29.0	74 700	89 900
		8.0	75.5	28.7	60 900	72 200
		9.0	73.3	28.4	51 300	60 200
		10.0	71.1	28.1	44 100	51 400
		11.0	68.9	27.8	38 600	44 800
		12.0	66.6	27.3	34 300	39 600
		14.0	62.0	26.4	27 700	31 900
		16.0	57.1	25.2	23 100	26 500
		18.0	52.0	23.8	19 700	22 600
		20.0	46.5	22.1	17 100	19 600
		22.0	40.4	20.0	15 000	17 200
		24.0	33.5	17.3	13 200	15 200
		26.0	24.9	13.7	11 800	13 600
30.5	100	5.8	81.2	32.3	101 800	110 200*
		6.0	80.8	32.3	96 000	110 200*
		7.0	78.9	32.1	74 500	90 200
		8.0	77.0	31.9	60 700	72 100
		9.0	75.0	31.6	51 000	60 000
		10.0	73.1	31.3	43 900	51 200
		11.0	71.1	31.0	38 400	44 600
		12.0	69.1	30.6	34 000	39 400
		14.0	65.0	29.8	27 500	31 700
		16.0	60.8	28.8	22 900	26 300
		18.0	56.4	27.5	19 500	22 300
		20.0	51.7	26.1	16 800	19 300
		22.0	46.8	24.4	14 700	16 900
		24.0	41.3	22.3	13 000	14 900
		26.0	35.3	19.8	11 500	13 300
		28.0	28.1	16.5	10 300	11 900
		30.0	18.6	11.9	9 300	10 800
33.5	110	6.1	81.5	35.3	93 200	97 900*
		7.0	79.9	35.2	74 300	91 500
		8.0	78.2	35.0	60 600	71 900
		9.0	76.4	34.8	50 900	59 800
		10.0	74.6	34.5	43 700	51 100
		11.0	72.9	34.2	38 200	44 400
		12.0	71.1	33.9	33 800	39 200
		14.0	67.4	33.1	27 300	31 500
		16.0	63.6	32.2	22 700	26 100
		18.0	59.8	31.1	19 300	22 200
		20.0	55.7	29.9	16 600	19 200
		22.0	51.5	28.4	14 500	16 700
		24.0	47.0	26.7	12 800	14 800
		26.0	42.1	24.6	11 400	13 100
		28.0	36.7	22.2	10 100	11 700
		30.0	30.5	19.2	9 100	10 600
		32.0	22.9	15.2	8 200	9 600
36.6	120	6.7	81.2	38.3	79 600	84 700*
		7.0	80.7	38.3	74 600	83 900*
		8.0	79.2	38.1	60 400	71 800
		9.0	77.6	37.9	50 800	59 700
		10.0	75.9	37.6	43 600	51 000
		11.0	74.3	37.4	38 100	44 300
		12.0	72.7	37.1	33 700	39 100
		14.0	69.4	36.4	27 200	31 400
		16.0	66.0	35.6	22 600	25 000
		18.0	62.5	34.6	19 100	22 000
		20.0	58.9	33.5	16 500	19 000
		22.0	55.2	32.2	14 300	16 600
		24.0	51.3	30.7	12 600	14 600
		26.0	47.1	29.0	11 200	13 000
		28.0	42.7	27.0	10 000	11 600
		30.0	37.8	24.6	8 900	10 400
		32.0	32.4	21.8	8 100	9 400
		34.0	26.0	18.2	7 300	8 500

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
39.6	130	7.3	81.0	41.3	69 200	83 100
		8.0	80.0	41.2	60 300	71 700
		9.0	78.5	41.0	50 600	59 600
		10.0	77.0	40.8	43 400	50 800
		11.0	75.6	40.5	37 900	44 100
		12.0	74.1	40.3	33 500	38 900
		14.0	71.0	39.6	27 000	31 200
		16.0	67.9	38.9	22 400	25 800
		18.0	64.8	38.0	19 000	21 800
		20.0	61.5	37.0	16 300	18 800
		22.0	58.2	35.8	14 200	16 400
		24.0	54.7	34.5	12 400	14 400
		26.0	51.1	33.0	11 000	12 800
		28.0	47.3	31.3	9 800	11 400
		30.0	43.2	29.3	8 800	10 200
		32.0	38.8	27.0	7 800	9 300
		34.0	33.9	24.3	7 100	8 400
		36.0	29.3	21.0	6 400	7 600
		38.0	21.4	16.6	5 800	6 900
42.7	140	7.9	80.9	44.3	61 000	71 200*
		8.0	80.7	44.3	60 200	70 300*
		9.0	79.4	44.1	50 400	59 500
		10.0	78.0	43.9	43 200	50 600
		11.0	76.6	43.7	37 700	43 900
		12.0	75.2	43.4	33 300	38 700
		14.0	72.4	42.8	26 700	31 000
		16.0	69.6	42.2	22 100	25 600
		18.0	66.7	41.4	18 700	21 600
		20.0	63.7	40.4	16 100	18 600
		22.0	60.7	39.4	13 900	16 100
		24.0	57.6	38.2	12 200	14 200
		26.0	54.3	36.8	10 700	12 500
		28.0	51.0	35.3	9 500	11 100
		30.0	47.4	33.6	8 500	10 000
		32.0	43.6	31.6	7 600	9 000
		34.0	39.6	29.4	6 800	8 100
		36.0	35.2	26.7	6 100	7 300
		38.0	30.2	23.6	5 500	6 600
		40.0	24.3	19.7	5 000	6 000
45.7	150	7.9	81.5	47.4	60 800	71 200*
		8.0	81.3	47.4	60 000	70 300*
		9.0	80.1	47.2	50 200	59 300
		10.0	78.8	47.0	43 000	50 400
		11.0	77.5	46.8	37 500	43 700
		12.0	76.2	46.6	33 100	38 500
		14.0	73.6	46.0	26 500	30 800
		16.0	71.0	45.4	21 900	25 400
		18.0	68.3	44.7	18 500	21 400
		20.0	65.6	43.8	15 800	18 400
		22.0	62.8	42.8	13 700	15 900
		24.0	60.0	41.7	12 000	14 000
		26.0	57.0	40.5	10 500	12 400
		28.0	54.0	39.1	9 300	11 000
		30.0	50.8	37.6	8 300	9 800
		32.0	47.5	35.9	7 400	8 800
		34.0	44.0	33.9	6 600	7 900
		36.0	40.3	31.7	5 900	7 100
		38.0	36.2	29.2	5 300	6 400
		40.0	31.7	26.2	4 700	5 800
		42.0	26.6	22.6	4 200	5 300
		44.0	20.3	18.0	3 800	4 800

Courtesy of Crane.Market

LIFTCRANE CAPACITIES

BOOM NO 22 WITH OPEN THROAT TOP
47 360 kg CRANE COUNTERWEIGHT
360 DEGREE RATING

Meets AS1418.5 Table 9.4.2.1 (a)

Meets ANSI B30.5 Requirements

4000 W

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
48.8	160	8.5	81.3	50.4	54 200	64 200
		9.0	80.7	50.3	50 100	59 200
		10.0	79.5	50.1	42 800	50 300
		11.0	78.3	49.9	37 300	43 600
		12.0	77.1	49.7	32 900	38 400
		14.0	74.7	49.2	26 400	30 600
		16.0	72.2	48.6	21 800	25 300
		18.0	69.7	47.9	18 300	21 300
		20.0	67.2	47.1	15 700	18 200
		22.0	64.6	46.2	13 500	15 800
		24.0	62.0	45.2	11 800	13 800
		26.0	59.3	44.1	10 400	12 200
		28.0	56.5	42.9	9 200	10 800
		30.0	53.7	41.5	8 100	9 600
		32.0	50.7	39.9	7 200	8 600
		34.0	47.5	38.2	6 400	7 700
		36.0	44.3	36.2	5 800	6 900
		38.0	40.9	34.1	5 100	6 200
		40.0	37.1	31.6	4 600	5 600
		42.0	33.0	28.8	4 100	5 100
		44.0	28.4	25.4	3 600	4 600
		46.0	23.0	21.2	3 200	4 200
51.8	170	9.1	81.1	53.4	48 700	57 200*
		10.0	80.1	53.2	42 700	50 200
		11.0	79.0	53.0	37 100	43 400
		12.0	77.9	52.8	32 800	38 200
		14.0	75.6	52.4	26 200	30 400
		16.0	73.3	51.8	21 600	25 100
		18.0	71.0	51.2	18 100	21 100
		20.0	68.6	50.4	15 500	18 000
		22.0	66.2	49.6	13 400	15 600
		24.0	63.8	48.7	11 600	13 600
		26.0	61.3	47.6	10 200	12 000
		28.0	58.7	46.5	9 000	10 600
		30.0	56.1	45.2	7 900	9 400
		32.0	53.4	43.8	7 000	8 400
		34.0	50.6	42.2	6 200	7 500
		36.0	47.7	40.5	5 500	6 700
		38.0	44.6	38.6	4 900	6 100
		40.0	41.4	36.4	4 400	5 400
		42.0	37.9	34.0	3 900	4 900
		44.0	34.1	31.3	3 400	4 400
		46.0	30.0	28.1	3 000	3 900
		48.0	25.2	24.2	2 600	3 500
		50.0	19.4	19.4	2 300	3 100
54.9	180	9.8	80.9	56.3	44 100	51 900
		10.0	80.7	56.3	42 600	50 000
		11.0	79.6	56.1	36 900	43 200
		12.0	78.6	55.9	32 500	38 000
		14.0	76.4	55.5	26 000	30 200
		16.0	74.3	55.0	21 300	24 800
		18.0	72.1	54.4	17 900	20 800
		20.0	69.9	53.7	15 200	17 800
		22.0	67.6	52.9	13 100	15 300
		24.0	65.3	52.0	11 400	13 400
		26.0	63.0	51.1	9 900	11 700
		28.0	60.7	50.0	8 700	10 300
		30.0	58.2	48.8	7 700	9 200
		32.0	55.7	47.5	6 800	8 200
		34.0	53.2	46.1	6 000	7 300
		36.0	50.5	44.5	5 300	6 500
		38.0	47.8	42.8	4 600	5 800
		40.0	44.9	40.9	4 100	5 200
		42.0	41.8	38.8	3 600	4 600
		44.0	38.6	36.4	3 200	4 100
		46.0	35.1	33.7	2 800	3 700
		48.0	31.3	30.7	2 400	3 300
		50.0	27.0	27.1	2 000	2 900
		52.0	22.0	22.7		2 600

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
57.9	190	9.8	81.4	59.4	43 900	51 700
		10.0	81.2	59.4	42 400	49 900
		11.0	80.2	59.2	36 700	43 100
		12.0	79.2	59.0	32 300	37 800
		14.0	77.1	58.6	25 800	30 000
		16.0	75.1	58.1	21 100	24 600
		18.0	73.1	57.6	17 700	20 700
		20.0	71.0	56.9	15 000	17 600
		22.0	68.9	56.2	12 900	15 100
		24.0	66.7	55.4	11 100	13 200
		26.0	64.6	54.5	9 700	11 500
		28.0	62.3	53.5	8 500	10 100
		30.0	60.1	52.4	7 400	9 000
		32.0	57.8	51.2	6 500	7 900
		34.0	55.4	49.8	5 800	7 100
		36.0	53.0	48.4	5 100	6 300
		38.0	50.4	46.8	4 500	5 600
		40.0	47.8	45.1	3 900	5 000
		42.0	45.1	43.2	3 400	4 400
		44.0	42.2	41.1	2 900	3 900
		46.0	39.2	38.8	2 500	3 500
		48.0	35.9	36.2	2 200	3 100
		50.0	32.4	33.2	1 800	2 700
		52.0	28.5	29.8		2 300
		54.0	24.1	25.8		2 000
61.0	200	10.4	81.2	62.4	40 000	43 300*
		11.0	80.7	62.3	36 600	43 000
		12.0	79.7	62.1	32 200	37 600
		14.0	77.8	61.7	25 600	29 900
		16.0	75.9	61.3	21 000	24 500
		18.0	73.9	60.7	17 500	20 500
		20.0	72.0	60.1	14 800	17 400
		22.0	70.0	59.4	12 700	15 000
		24.0	68.0	58.7	11 000	13 000
		26.0	65.9	57.8	9 600	11 400
		28.0	63.8	56.9	8 300	10 000
		30.0	61.7	55.8	7 300	8 800
		32.0	59.6	54.7	6 300	7 800
		34.0	57.4	53.5	5 600	6 900
		36.0	55.1	52.2	4 900	6 100
		38.0	52.8	50.7	4 200	5 400
		40.0	50.4	49.1	3 700	4 800
		42.0	47.9	47.4	3 200	4 200
		44.0	45.3	45.5	2 800	3 700
		46.0	42.6	43.4	2 300	3 300
		48.0	39.7	41.1	2 000	2 800
		50.0	36.7	38.6		2 500
		52.0	33.4	35.7		2 100
64.0	210	11.0	81.1	65.4	36 500	42 900
		12.0	80.2	65.2	32 000	37 400
		14.0	78.4	64.9	25 400	29 700
		16.0	76.6	64.4	20 700	24 300
		18.0	74.7	63.9	17 300	20 300
		20.0	72.8	63.3	14 600	17 200
		22.0	71.0	62.7	12 500	14 800
		24.0	69.1	61.9	10 800	12 800
		26.0	67.1	61.1	9 300	11 100
		28.0	65.2	60.3	8 100	9 700
		30.0	63.2	59.3	7 100	8 600
		32.0	61.2	58.2	6 200	7 600
		34.0	59.1	57.1	5 400	6 700
		36.0	57.0	55.8	4 700	5 900
		38.0	54.8	54.5	4 100	5 200
		40.0	52.6	53.0	3 500	4 600
		42.0	50.3	51.4	3 000	4 000
		44.0	47.9	49.7	2 600	3 500
		46.0	45.5	47.8	2 200	3 100
		48.0	42.9	45.7		2 700
		50.0	40.2	43.5		2 300

Courtesy of Crane.Market

MANITOWOC ENGINEERING CO.
Division of The Manitowoc Company, Inc. Manitowoc. Wisconsin 54220

LIFTCRANE CAPACITIES

BOOM NO 22 WITH OPEN THROAT TOP
47 360 kg CRANE COUNTERWEIGHT
360 DEGREE RATING

Meets
AS1418.5
Table 9.4.2.1 (a)

Meets
ANSI B30.5
Requirements

4000 W

BOOM LGTH. METERS	BOOM LGTH. FEET	OPER. RADIUS METERS	BOOM ANG. DEG.	BOOM POINT ELEV. METERS	CAPACITY CRAWLERS RETRACTED KILOGRAMS	CAPACITY CRAWLERS EXTENDED KILOGRAMS
67.1	220	11.6	81.0	68.4	33 500	39 300
		12.0	80.7	68.3	31 800	37 300
		14.0	78.9	68.0	25 200	29 500
		16.0	77.2	67.5	20 500	24 100
		18.0	75.4	67.1	17 100	20 000
		20.0	73.6	66.5	14 400	17 000
		22.0	71.9	65.9	12 300	14 500
		24.0	70.0	65.2	10 500	12 500
		26.0	68.2	64.4	9 100	10 900
		28.0	66.4	63.6	7 900	9 500
		30.0	64.5	62.7	6 800	8 300
		32.0	62.6	61.7	5 900	7 300
		34.0	60.6	60.6	5 100	6 400
		36.0	58.7	59.4	4 400	5 600
		38.0	56.6	58.2	3 800	5 000
		40.0	54.6	56.8	3 300	4 300
		42.0	52.4	55.3	2 700	3 800
		44.0	50.2	53.7	2 300	3 300
		46.0	48.0	52.0		2 800
		48.0	45.6	50.1		2 400
		50.0	43.2	48.1		2 000

Courtesy of Crane.Market