



One Size Does Not Fit All.

Matrax Composite Outrigger Pads

IDEAL STRENGTH/WEIGHT RATIO

FEATURES/SPECS

- Watertight welded design
- Lightweight yet durable
- Handles for lifting
- Easy to maintain
- Available in grey & white
- Square sizes available: 40", 24", 19.5"
- Volume discounts available: call for pricing

APPLICATIONS

The Matrax HDPE outrigger pads are designed to support utility trucks, tree trimmers, concrete pumps, cranes, fire trucks, and aerial equipment.



Specification	Standard	Metric
Net Working Surface	8.72 ft ²	0.81 m ²
Weight	50 lbs	22.68 kg
Surface Dimensions	40 in	101.6 cm
Height	3 in	7.62 cm
Compression Strength	450 psi	3,100 kpa
Min. Contact for Static Loads >250 lbs	16 in ²	10.16 cm ²
Max. Allowable Deflection	3 in	7.62 cm
Temperature Range	-4°F – 113° F	-20°C – 45°C
Burn Rating	UL 94-HB	

Ground conditions can vary considerably from location to location and exhibit variable soil bearing pressures. These conditions will have an impact on the performance of the outrigger pads. As a rule of measure, the maximum allowable deflections of the outrigger pads should not exceed 3 inches.