

>> SPEED SWING 445E

SPECIFICATIONS



Designed to tackle a variety of rail applications, the Pettibone® Speed Swing™ 445E is a versatile machine that provides the power to lay rails, set ties or clear the path ahead. The unit features a turbo diesel engine and 180-degree boom rotation for enhanced productivity. Offering precise hydraulics, numerous attachments and the ability to work both on and off the rails, the Speed Swing 445E is equipped for any rail task.

SPECIFICATIONS



DIMENSIONS	
1 Height 10' 9" (328 cm)	
2 Length 22' 11" (698 cm)	
Width 8' 8" (264 cm)	
Weight 31,217 lbs (14,160 kg) with Hi-rail 26,217 lbs (11,892 kg) without Hi-rail	
ENGINE	
Model/Power 160 HP (119 kW) Cummins® QSB6.7	
Fuel Tank 52 gal. (197 L)	
Heating Engine block heater	
HYDRAULICS	
Controls Dual pilot operated	
Tank 75 gal. (284 L)	
Gear Pump 19 gpm (72 LPM) at 2,400 RPM for lift, tilt, auxilian	I
Piston Pump 38 gpm (144 LPM) at 2,400 RPM for Hi-rail, swing generator, tool circuit	
PERFORMANCE	
Max Load Capacity (On Tires) 10,000 lbs (4,536 kg) front 8,000 lbs (3,629 kg) side	
Max Load Capacity (On Hi-Rail) 10,000 lbs (4,536 kg) front 5,400 lbs (2,449 kg) side	
Boom Rotation 180°	
Maximum Travel Speed 25 mph (40 km/h)	
Transmission Dana® T20000; twist grip electric shift control	
Drive 4-wheel with rear wheel disconnect; hi/low rang	9
Brakes 4-wheel outboard dry disc service brakes, manu park break	3

FEATURES & OPTIONS

OPERATOR CAB			
ROPS/FOPS with tinted safety glass Front and rear window wipes	Tilting cab enclosure Full instrumentation panel		
AVAILABLE ATTACHMENTS			
Drawbar coupler Rail threader Magnet Switch broom Auger Grapple Clamshell Cribbing bucket V-type snow plow Back filler blade	Loader bucket Track cleaning bucket Snow bucket Extendable boom Lattice boom Tote hooks Backhoe Brush cutter Front-mounted winch		
OPTIONS			
Hi-rails (insulated or non) Hi-Rail pin type locks Tachometer Warning beacon Rail sanders Train brakes Turnable pin type lock Passenger seat Air conditioner Cab heater	Emergency power unit Machine fluid heaters Hydraulic top-off system Rear window defroster Turn signals/hazard lights Lighting package Front and rear fenders Heavy-duty rear bumper Vandal covers Spare tire carrier		

^{*} Specifications are subject to change.



PETTIBONE, LLC

1100 Superior Avenue Baraga, MI 49908

P: 800.467.3884 info@gopettibone.com www.gopettibone.com

		WARRANTY
	1 Year	Full machine and attachment
1-2-3 WARRANTY	2 Years	Powertrain and major hydraulic components
	3 Years	Machine structure