


AS3246/AS3246E MOBILE ELEVATING WORK PLATFORMS

Offering electric or hydraulic motor drive configurations, the Pettibone AS3246E and AS3246 mobile elevating work platforms provide personnel with a reliable, reinforced lift for safely working indoors at heights up to 39.4 feet.



SPECIFICATIONS



AS3246E

AS3246

DIMENSIONS

1	Overall Height	6.1' (186 cm) - rails down 8' (244 cm) - rails up	6.1' (186 cm) - rails down 8' (244 cm) - rails up
2	Platform Extension	3' (91 cm)	3' (91 cm)
3	Overall Length	8.1' (247 cm)	8.1' (247 cm)
4	Overall Width	3.9' (119 cm)	3.9' (119 cm)
	Work Height	39.4' (1,201 cm)	39.4' (1,201 cm)
	Machine Weight	6,614 lbs (3,000 kg)	6,614 lbs (3,000 kg)

PERFORMANCE

	Platform Capacity	705 lbs (320 kg)	705 lbs (320 kg)
	On-Deck Extension Capacity	265 lbs (120 kg)	265 lbs (120 kg)
	Platform Occupants	2 - indoor 1 - outdoor	2 - indoor 1 - outdoor
	Drive Speed	Lowered: 2.2 ± 0.12 mph (3.5 ± 0.19 km/h) Elevated: 0.5 ± 0.06 mph (0.8 ± 0.1 km/h)	Lowered: 1.9 ± 0.12 mph (3.1 ± 0.19 km/h) Elevated: 0.5 ± 0.06 mph (0.8 ± 0.1 km/h)
	Lift Time	58 ± 4 seconds	62 ± 4 seconds
	Lower Time	48 ± 4 seconds	48 ± 4 seconds
	Gradeability	25%	25%
	Maximum Slope	2° / 3°	2° / 3°
	Maximum Ground Pressure	173.8 psi	173.8 psi
	Inside Turning Radius	13" (33 cm)	13" (33 cm)
	Outside Turning Radius	7.5' (229 cm)	7.5' (229 cm)
	Standards Compliance	ANSI A92.20 CSA-B354.6	ANSI A92.20 CSA-B354.6

FEATURES & OPTIONS

FEATURES

Optimized electronic control system	Motion alarm
Optimized hydraulic system	Flashing beacon/buzzer
Universal drive control box	Emergency descent
Proportional control	Descent alarm and protection
Quick disconnect for control box	Overload alarm
Emergency stop device	Horn/hour meter
Platform power 120VAC (GFCI)	4x2 drive
Foot pedal control for platform extension	Extra wide, non-marking tires
Fold-in guard rails	Pothole guards
Self-closing, self-catching entry gate	Two-wheel brake
Lanyard anchor point	Manual brake release
Large scissor arms	Advanced battery charger with voltage protection
Pressure transducer	Slide-out component tray
Full-height drive	Charging status indicator
Intelligent diagnostic system	Charging operation limit
Tilt sensor and alarm	
Slope sensor	

* Specifications are subject to change.

WARRANTY

PETTIBONE®

PETTIBONE, LLC

1100 Superior Avenue
Baraga, MI 49908

P: 800.467.3884
info@gopettibone.com
www.gopettibone.com

**1 - 2 - 5
WARRANTY**

1 Year

Full machine and attachment

2 Years
or 2,000 hrs

Electric & hydraulic drive motors, lift cylinders, hydraulic valves, & hydraulic pumps

5 Years

Frame weldment, scissor stacks & platform weldment