




MOBILE ELEVATING WORK PLATFORM

Offering an electric motor drive configuration, the Pettibone SS1230E mobile elevating work platform provides personnel with a reliable, reinforced lift for safely working indoors at heights up to 18.4 feet.



SPECIFICATIONS



SS1230E

| DIMENSIONS | | |
|----------------------------|---|--|
| 1 Overall Height | 6' (183 cm) - rails down 6.8' (207 cm) - rails up | |
| 2 Platform Extension | 2' (61 cm) | |
| 3 Overall Length | 5' (152 cm) | |
| 4 Overall Width | 2.5' (76 cm) | |
| Work Height | 18.4' (561 cm) | |
| Machine Weight | 1,940 lbs (880 kg) | |
| PERFORMANCE | | |
| Platform Capacity | 530 lbs (240 kg) | |
| On-Deck Extension Capacity | 265 lbs (120 kg) | |
| Platform Occupants | 2 - indoor 1 - outdoor | |
| Drive Speed | Lowered: 2.2 ± 0.12 mph (3.5 ± 0.19 km/h) Elevated: 0.3 ± 0.06 mph (0.5 ± 0.1 km/h) | |
| Lift Time | 25 ± 2 seconds | |
| Lower Time | 20 ± 2 seconds | |
| Gradeability | 25% | |
| Maximum Slope | 1.5° / 3° | |
| Maximum Ground Pressure | 172.3 psi | |
| Inside Turning Radius | 8" (20 cm) | |
| Outside Turning Radius | 4.9' (149 cm) | |
| Standards Compliance | ANSI A92.20 CSA-B354.6 | |

FEATURES & OPTIONS

FEATURES

Slope sensor

Optimized electronic control system
Universal drive control box
Proportional control
Quick disconnect for control box
Emergency stop device
Platform power 120VAC (GFCI)
Foot pedal control for platform extension
Fold-in guard rails
Self-closing, self-catching entry gate
Lanyard anchor point
Large scissor arms
Pressure transducer
Full-height drive
Intelligent diagnostic system
Tilt sensor and alarm

Motion alarm
Flashing beacon/buzzer
Emergency descent
Descent alarm and protection
Overload alarm
Horn/hour meter
4x2 drive
Extra wide, non-marking tires
Pothole guards
Two-wheel brake
Manual brake release
Advanced battery charger with voltage
protection
Slide-out component tray

Charging status indicator

Charging operation limit



PETTIBONE. LLC

1100 Superior Avenue Baraga, MI 49908

P: 800.467.3884 info@gopettibone.com www.gopettibone.com

| | | WARRANTY |
|-----------------------|-------------------------|---|
| | 1 Year | Full machine and attachment |
| 1 - 2 - 5 WARRANTY | 2 Years or 2,000 hrs | Electric & hydraulic drive motors, lift cylinders, hydraulic valves, & hydraulic pumps |
| | 5 Years | Frame weldment, scissor stacks & platform weldment |

^{*} Specifications are subject to change.