



Performance

Maximum Lifting Capacity -7,000 lbs (3,175 kg)

Maximum Lift Height -36' (10.97 m)

Maximum Forward Reach -24' (7.3 m) (at 24" Load Center)

Below Grade Reach

-3' (0.9 m)

Maximum Travel Speed

- 20 mph (32 km/h)

- 24° of Leveling (12° right and left)
- Fits Under 8' (2.4 m) Doorway

Turning Radius

- 12′ 6″ (3.8 m)

Standard Equipment

- Cummins 110 hp Tier III Turbo Diesel with Electronic Control and Protection
- 32.6 Gallon (123.4 L) Fuel Tank

Transmission

- -Fully Modulated Carraro Powershift
- Four Speed Forward and Reverse
- Parking Brake Engaged Transmission Declutch

- Four-wheel Drive
- Carraro Outboard Planetary Axles

- Four-wheel, Two-wheel, and Crab Steer

Brakes

- Oil-immersed, Inboard Disc Service Brakes
- Integral Park Brake

Tires

- 13.00 x 24, 14 ply

Boom

- Automatic Fork Leveling Without Slave
- Two Wide-stance, Heavy-duty Lift Cylinders GPS Equipment Management System

- -Unmatched Visibility
- Adjustable Suspension Seat with Seat Belt
- Full Set of Gauges for Instant Machine
- Fully Adjustable Right-side Arm Rest

- **Hydraulics** Piston Pump
- Rapid Response Hydraulic System
- Auxiliary Boom Tip Hydraulics
- Quick Disconnect for Attachments
- Single Joystick for all boom functions

Attachment

- 48" (1.2 m) Standard Fork Carriage 2x4x48" Standard Pallet Forks


Optional Equipment

- Light Packages
- Foam Filled Tires
- Enclosed Cab (HWD)



Extendo[™] Series





Dimensions

Height 88.5" (2.3 m) Boom Down

Length 19' 7" (6.0 m) to Fork Frame

Width 102" (2.6 m)

Ground Clearance 18" (0.5 m)

Curb Weight (approximate) 21,720 lbs (9,852 kg)

Optional Attachments

- Pallet, Lumber and Block Forks
- -Side Tilt Carriages ±10°
- Truss Boom
- Utility Buckets

Contact Information

Pettibone

1100 Superior Avenue Baraga, MI 49908 800.GO.PETTIBONE

gopettibone.com

NOTE: The Company reserves the right to change specifications and prices without notice in order to follow its policy of constantly striving to manufacture a better product without incurring any liability to provide these new features on any units previously manufactured. Prices and specifications subject to change without notice.