

pecolift
3.5m Non-Powered, Powered Access

ecolift
4.2m Non-Powered, Powered Access



**BATTERY FREE
POWER FREE
OIL FREE
EASY! FAST! SAFE!
AWARD WINNING**



Step in.



Simply turn the handle...




...3.5m working height in 11 seconds.

pecolift

3.5m Non-Powered, Powered Access



3.5m



OPERATING SPECIFICATIONS - Pecolift

Working Dimensions

	Standard	Wind Rated
Maximum working height:	3.50 m	
Maximum platform height:	1.50 m	
Basket dimensions:	0.72 m (L) x 0.60 m (W)	
Working footprint:	0.98 m x 0.70 m	1.10m x 1.10m
Safe working load:	150 kg (1 person + tools)	
Maximum manual force:	200 N	
Maximum gradient for operation:	0 degrees	3°
Maximum wind force:	Internal use only, 0 (zero) mph	Internal/ External Use. 28mph.
Maximum wheel force:	125 kg	195 kg
Maximum castor point load:	125 kg (1.23 kN)	195 kg (1.91kN)
Sound pressure level:	Less than 70DbA	

Closed Dimensions

Length:	0.98 m	1.10 m
Width:	0.70 m	1.10 m
Height:	1.55 m	1.55 m
Weight:	180 kg	240 kg


Lift Cycles

Unlimited	Unlimited
-----------	-----------



WIND RATED

Available as an option to the standard machine, Pecolift Wind Rated is operable on gradients up to 3° and in winds up to 28mph.





4.2m

2.2m



OPERATING SPECIFICATIONS - Ecolift

Working Dimensions

	Standard	Wind Rated
Maximum working height:	4.20 m	
Maximum platform height:	2.20 m	
Basket dimensions:	850 mm (L) x 644 mm (W)	
Working footprint:	1.28 m x 700 mm	1.28m x 950mm
Safe working load:	150 kg (1 person + tools)	
Maximum manual force:	200 N	
Maximum gradient for operation:	0 degrees	3°
Maximum wind force:	Internal use only, 0 (zero) mph	Internal/ External Use. 28mph. 245 kg (2.4kN)
Maximum wheel force:	234 kg	
Maximum castor point load:	234 kg (2.29 kN)	
Sound pressure level:	Less than 70DbA	

Closed Dimensions

Length:	1.28 m	1.28 m
Width:	0.70 m	0.95 m
Height:	1.94 m	1.94 m
Weight:	305 kg	335 kg

Lift Cycles

Unlimited	Unlimited
-----------	-----------



WIND RATED

Available as an option to the standard machine, Ecolift Wind Rated is operable on gradients up to 3° and in winds up to 28mph.



work smart

...IT PAYS TO SPECIFY POWER TOWERS

Power Towers' products offer proven productivity gains - up to 8 times faster than traditional methods of access using podiums and towers.



Non-powered Powered Access! ...a major step change in low-level access.

It's so easy, fast and efficient to use, it's intuitive. Just step in and turn the handle! And you don't need power; no batteries to charge or mains power consumption. We call it 'non-powered powered access!'©

Gone are the days of climbing steps or podiums, no more slips, trips or having to balance!

Stop wherever you want up to 4.2m working height.

You're always safe, fully guarded from the ground up. And its low maintenance, in fact it's virtually maintenance free, it's so simple!

- Step into the platform, no climbing.
- Intuitive to operate - turn handle to elevate. Patented* lift mechanism, no power required.
- 'Auto-lok' brake on elevation.
- Lightweight, easy to manoeuvre.
- Small footprint
- Unlimited lift cycles, can be used 24/7.
- Robust design for years of trouble free service.
- Minimal operational costs, virtually maintenance free.



eco compliant

Power Towers is committed to eco friendly manufacture. Our Eco range of products are hydraulic oil and battery free, and with no need to charge, have no energy consumption. They are an Eco friendly solution to your Powered Access needs.

This brochure and associated data is intended as a guide only and as such is not legally binding, nor does it form part of any contract. All dimensions are approximate.

Power Towers' products are 100% designed and manufactured in the UK.

*Patent applied for.



Power Towers Limited
West House, West Avenue,
Wigston, Leicester
LE18 2FB UK

Tel: +44 (0)116 200 1757

Fax: +44 (0)116 284 9243

powertowers.com | pecolift.com
sales@powertowers.com



Courtesy of Crane.Market