





PB45

Load Capacity @ 24" load center 4,500 lb 5,000 lb. (4500 lb LP*) Engine - Diesel CAT® Horsepower 36 HP Driven Wheels 3 3 Personnel Alert Package Yes Yes (LP) Deluxe Seat and Steering Wheel No Yes (Not available on LP*) Anti Stall Hydraulic Control Yes Weather Shield No No Weather Shield No No No Prescretains Tool Box No No No No Prescretains		Features	Options
Horsepower 36 HP Driven Wheels 3 3 3 3 3 3 Personnel Alert Package Yes Yes (LP) Deluxe Seat and Steering Wheel No Yes (Not available on LP*) Anti Stall Hydraulic Control Yes Weather Shield No Yes (Includes LP) Tool Box No No No Pre-Cleaner No No Pre-Cleaner No Brakes Dual, Front Tires 29"x12".5" (26"x12"x12" (on LP*) (Sand Tire) Sealed Tires Yes Yes Speed 7 mph Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No Side Shield Support Arms No Support Arms Side Shield	Load Capacity @ 24" load center	4,500 lb	5,000 lb. (4500 lb LP *)
Driven Wheels Personnel Alert Package Personnel Alert	Engine - Diesel	CAT®	
Personnel Alert Package Deluxe Seat and Steering Wheel Anti Stall Hydraulic Control Weather Shield No Yes Weather Shield No No Pre-Cleaner No Brakes Dual, Front Tires 29"x12".5" (pneumatic) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius Lift Height 86" 120"/144" (86" on LP") Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift Height, mast lowered Reach Scissors or Moving Mast Hose Rupture Protection Yes Support Arms No Yes (Not available on LP*) Yes (Not available on LP*) Yes (Includes LP) No No Yes (Includes LP)	Horsepower	36 HP	
Deluxe Seat and Steering Wheel No Yes (Not available on LP*) Anti Stall Hydraulic Control Yes Weather Shield No Yes (Includes LP) Tool Box No No Pre-Cleaner No Brakes Dual, Front Tires 29"x12".5" 26"x12"x12" (on LP*) (pneumatic) (Sand Tire) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius 186" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms	Driven Wheels	3	3
Anti Stall Hydraulic Control Weather Shield No Ves (Includes LP) Tool Box No No Pre-Cleaner No Brakes Dual, Front Tires 29"x12".5" (pneumatic) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift Height, mast lowered Reach Scissors or Moving Mast Hose Rupture Protection Seat Belt Interlock Ves Support Arms No	Personnel Alert Package	Yes	Yes (LP)
Weather Shield No No No Pre-Cleaner No Brakes Dual, Front Tires 29"x12".5" (pneumatic) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift Height, mast lowered 86" 81" (Only on LP*) Reach Hose Rupture Protection Yes Support Arms No Yes (Includes LP) No No No No No Yes (Includes LP) No No	Deluxe Seat and Steering Wheel	No	Yes (Not available on LP*)
Tool Box No No Pre-Cleaner No Brakes Brakes Dual, Front 29"x12".5" (pneumatic) 26"x12"x12" (on LP*) (Sand Tire) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*)	Anti Stall Hydraulic Control	Yes	
Pre-Cleaner No Brakes Dual, Front Tires 29"x12".5" (pneumatic) 26"x12"x12" (on LP*) (Sand Tire) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back Side Shift 5.5"/7" Side Shift Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Weather Shield	No	Yes (Includes LP)
Brakes Dual, Front Tires 29"x12".5" (pneumatic) 26"x12"x12" (on LP*) (Sand Tire) Sealed Tires Yes Speed Speed 7 mph Gradeability Turning Radius 78" Lift Height Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back Side Shift 5.5"/7" Side Shift Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Tool Box	No	No
Tires 29"x12".5" (pneumatic) 26"x12"x12" (on LP*) (Sand Tire) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Pre-Cleaner	No	
(pneumatic) (Sand Tire) Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 46" Height, mast lowered 86" 81" (Only on LP*) Reach Hose Rupture Protection Yes Seat Belt Interlock Overhead Guard (FOP/ROP) Protection Yes Support Arms No	Brakes	Dual, Front	
Sealed Tires Yes Speed 7 mph Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Tires	29"x12".5"	26"x12"x12" (on LP*)
Speed 7 mph Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP") Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No		(pneumatic)	(Sand Tire)
Gradeability 40% Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Sealed Tires	Yes	
Turning Radius 78" Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Speed	7 mph	
Lift Height 86" 120"/144" (86" on LP*) Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Gradeability	40%	
Weight* 5,250 lb Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Turning Radius	78"	
Tilt Forward/Back 5.5"/7" Side Shift 5.5" Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Lift Height	86"	120"/144" (86" on LP*)
Side Shift Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Weight*	5,250 lb	
Height, mast lowered 86" 81" (Only on LP*) Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Tilt Forward/Back	5.5"/7"	
Reach Scissors or Moving Mast Hose Rupture Protection Yes Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Side Shift	5.5"	
Hose Rupture Protection Seat Belt Interlock Overhead Guard (FOP/ROP) Protection Support Arms Yes Weather Shield Yes No	Height, mast lowered	86"	81" (Only on LP*)
Seat Belt Interlock Yes Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Reach	Scissors or Moving Mast	
Overhead Guard (FOP/ROP) Yes Weather Shield Protection Yes Support Arms No	Hose Rupture Protection	Yes	
Protection Yes Support Arms No	Seat Belt Interlock	Yes	
Support Arms No	Overhead Guard (FOP/ROP)	Yes	Weather Shield
The state of the s	Protection	Yes	
	Support Arms	No	
Mounting System Easy Hitch® Moffett Mount	Mounting System	Easy Hitch®	Moffett Mount
Overall Width 98"	Overall Width	98"	
Cargo Bay Width 62"	Cargo Bay Width	62"	
Overall Length 106.5"	Overall Length	106.5"	
Overhang 61" 65"	Overhang	61"	65"
Length under Truck 23" 29"	Length under Truck	23"	29"
Ground Clearance 11" 8.5" (LP*)	Ground Clearance	11"	8.5" (LP*)
Warranty 1 year 24 /36 months	Warranty	1 year	24 /36 months



PB50

	Features	Options
Load Capacity @ 24" load center	5,000 lb	5,500 lb.
Engine - Diesel	Kubota®	Kubota®
Horsepower	49 HP @2700 rpm	59 HP @2700 rpm
Driven Wheels	3	
Personnel Alert Package	Yes	
Deluxe Seat and Steering Wheel	No	Yes
Anti Stall Hydraulic Control	Yes	
Weather Shield	No	Yes
Tool Box	No	Yes
Pre-Cleaner	No	Yes
Brakes	Dual, Front	
Tires	31"x15.5"x15" (pneumatic)	Turf/Sand Tire
Sealed Tires	Yes	
Speed	7.5 mph	9 mph
Gradeability	50+%	
Turning Radius	78"	
Lift Height	86"	120"/144"/154"
Weight*	5,900 lb	6025./6160./6650 lb.
Tilt Forward/Back	8°/6°	
Side Shift	6.25"	
Height, mast lowered	100"	101"/110" /118"
Reach	Moving Mast	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	Weather Shield
Support Arms	No	Yes
Mounting System	Easy Hitch®	Moffett Mount
Overall Width	101"	
Cargo Bay Width	58.5"	
Overall Length	111" w/o Forks	
Overhang	80"	
Length under Truck	23"	
Ground Clearance	12"	
Warranty	1 year	4/36 months

Special Options and Packages, available * Low-Profile Model Weight, includes mast, forks, full size tires & fluids

Special Options and Packages, available

* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp.



PB70

	7,000 lb Kubota® Turbo	
Engine - Diesel K	Kubota® Turbo	
Horsepower 5	59 HP @2700 rpm	
Driven Wheels	3	
Personnel Alert Package Y	Yes	
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	Yes	
Weather Shield Y	Yes	
Tool Box Y	Yes	
Pre-Cleaner Y	Yes	
Brakes	Dual, Front	
	31"x15.5"x15" (pneumatic)	
Sealed Tires	Yes	
Speed 7	7.5 mph	
Gradeability 5	50+%	
Turning Radius 8	82"	
Lift Height 8	86"	120"/144"
Weight*	6,860 lb	6,990 lb./7,080 lb.
Tilt Forward/Back	8°/6°	
Side Shift 6	6.25"	
Height, mast lowered 1	100"	101"/110"
Reach	Moving Mast	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	
Support Arms	No	Yes
Mounting System E	Easy Hitch®	Moffett Mount
Overall Width 1	101"	
Cargo Bay Width 5	58.5"	
· ·	117" w/o Forks	
Overhang 8	80"	
Length under Truck	28"	
Ground Clearance 1	12"	
Warranty 1	1 year	24/36 months



PB80

	Features	Options
Load Capacity @ 24" load center	8,000 lb	
Engine - Diesel	Kubota®	
Horsepower	59 HP @2700 rpm	
Driven Wheels	3	
Personnel Alert Package	Yes	
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	Yes	
Weather Shield	Yes	
Tool Box	Yes	
Pre-Cleaner	Yes	
Brakes	Dual, Front	
Tires	31"x15.5"x15" (pneumatic)	
Sealed Tires	Yes	
Speed	7.5 mph	
Gradeability	50+%	
Turning Radius	82"	
Lift Height	86"	120"/144"
Weight*	7,130 lb	7,300 lb./7,420 lb.
Tilt Forward/Back	8°/6°	
Side Shift	6.25"	
Height, mast lowered	100"	101"/110"
Reach	Moving Mast	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	
Support Arms	No	Yes
Mounting System	Easy Hitch®	Moffett Mount
Overall Width	101"	
Cargo Bay Width	58.5"	
Overall Length	117" w/o Forks	
Overhang	80"	
Length under Truck	28"	
Ground Clearance	12"	
Warranty	1 year	24/36 months

Special Options and Packages, available
* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp.

Special Options and Packages, available
* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp.



PBX

IDA	Features	Options
Load Capacity @ 24" load center	5,000 lb	•
Engine - Diesel	Kubota®	Kubota® Turbo
Horsepower	49 HP @2700 rpm	59 HP @2700 rpm
Driven Wheels	3	
Personnel Alert Package	Yes	
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	Yes	
Weather Shield	Yes	
Tool Box	Yes	
Pre-Cleaner	No	Yes
Brakes	Dual, Front	
Tires	31"x15.5"x15"	
	(pneumatic)	Turf/Sand Tire
Sealed Tires	Yes	
Speed	7.5 mph	9 mph
Gradeability	50+%	
Turning Radius	82"	
Lift Height	86"	120"/144"
Weight*	6,790 lb	6,915 lb. / 7,050 lb
Tilt Forward/Back	8°/6°	
Side Shift	6.25"	
Height, mast lowered	100"	101"/110"
Reach	S.O.L.O.	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	
Support Arms	No	Yes
Mounting System	Easy Hitch®	Moffett Mount
Overall Width	101"	
Cargo Bay Width	58.5"	
Overall Length	117" w/o Forks	
Overhang	85"	
Length under Truck	23"	
Ground Clearance	12"	
Warranty	1 year	24/36 months

Special Options and Packages, available
* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp.



PBL

I DL		
	Features	Options
Load Capacity @ 24" load center	5,500 lb	
Engine - Diesel	Kubota® Turbo	
Horsepower	59 HP @2700 rpm	
Driven Wheels	3	
Personnel Alert Package	Yes	
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	Yes	
Weather Shield	Yes	
Tool Box	Yes	
Pre-Cleaner	Yes	
Brakes	Dual, Front	
Tires	31"x15.5"x15" (pneumatic)	Turf/Sand Tires
Sealed Tires	Yes	
Speed	7.5 mph	9 mph
Gradeability	50+%	
Turning Radius	82"	
Lift Height	86"	120"/144"
Weight*	6,860 lb	6,945 lb. / 7,080 lb.
Tilt Forward/Back	16°/8°	
Side Shift	6.25"	
Height, mast lowered	100"	101"/110"
Reach	Moving Mast	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	
Support Arms	Yes	
Mounting System	Easy Hitch®	Moffett Mount
Overall Width	101"	
Cargo Bay Width	58.5"	
Overall Length	117" w/o Forks	
Overhang	80"	
Length under Truck	28"	
Ground Clearance	12"	
Warranty	1 year	24/36 months

Special Options and Packages, available
* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp



D45

D-10		
	Features	Options
Load Capacity @ 24" load center	4,500 lb	5,500 lb.
Engine - Diesel	Kubota®	Kubota® Turbo
Horsepower	49 HP @2700 rpm	59 HP @2700 rpm
Driven Wheels	2	
Personnel Alert Package	No	Yes
Deluxe Seat and Steering Wheel	No	Yes
Anti Stall Hydraulic Control	No	
Weather Shield	No	Yes
Tool Box	No	Yes
Pre-Cleaner	No	Yes
Brakes	Dual, Front	
Front Tires	31"x15.5"x15" (pneumatic)	Turf/Sand Tire
Rear Tires	18.5"x8.5"x8" (pneumatic)	Filled/Sealed
Sealed Tires	Yes (Front)	Yes (Rear)
Speed	8.8 mph	12 mph
Gradeability	45%	
Turning Radius	76"	
Lift Height	86"	120"/144"
Weight*	5,325 lb	5.460 lb. / 5,550 lb.
Tilt Forward/Back	8°/6°	
Side Shift	No	6.25"
Height, mast lowered	100"	100"/110"
Reach	Moving Mast	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	Weather Shield
Support Arms	No	Yes
Mounting System	Easy Hitch®	Moffett Mount
Overall Width	100"	
Cargo Bay Width	58.5"	
Overall Length	104" w/o Forks	
Overhang	76"	
Length under Truck	28"	
Ground Clearance	12"	
Warranty	1 year	24/36 months

Special Options and Packages, available

* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp



E50


	Features	Options
Load Capacity @ 24" load center	5,000 lb	
Engine - Diesel	Kubota®	
Horsepower	48 HP @2700 rpm	
Driven Wheels	3	
Personnel Alert Package	Yes	
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	Yes	
Weather Shield	Yes	
Tool Box	No	Yes
Pre-Cleaner	No	Yes
Brakes	Yes (rear)	
Front Tires	31"x10"x16.5" (pneumatic)	Turf/Sand Tire
Rear Tires	31"x15.5"x15" (pneumatic)	Turf/Sand Tire
Sealed Tires	No	Yes
Speed	5.6 mph	
Gradeability	45%	
Turning Radius	90"	
Lift Height	86"	120"/138"
Weight*	5,400 lb	5,500 lb. / 5,650 lb
Tilt Forward/Back	7.5°/6.5°	
Side Shift	6.5"	
Height, mast lowered	96"	101"/110"
Reach	Scissors Reach	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	
Support Arms	No	Yes
Mounting System	Easy Mount/Easy-Hi	tch®/Moffett Mount
Overall Width	101"	
Cargo Bay Width	59"	
Overall Length	108" w/o Forks	
Overhang	72"	
Length under Truck	34"	
Ground Clearance	12"	
Warranty	1 year	24/36 months

Special Options and Packages, available
* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp



E50-S

	Features	Options
Load Capacity @ 24" load center	5,000 lb	
Engine - Diesel	Kubota®	
Horsepower	48 HP @2700 rpm	
Driven Wheels	3	
Personnel Alert Package	Yes	
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	Yes	
Weather Shield	Yes	
Tool Box	No	Yes
Pre-Cleaner	Yes	
Brakes	Yes (rear)	
Front Tires	31"x10"x16.5" (pneumatic)	Turf/Sand
Rear Tires	31"x15.5"x15" (pneumatic)	Turf/Sand
Sealed Tires	No	Yes
Speed	7.5 mph	
Gradeability	45% (Std Direction)	30% (4-Way Direction)
Turning Radius	90" (Regular)	63" (4-Way)
Lift Height	138"	120"
Weight*	6,215 lb	6,065 lb.
Tilt Forward/Back	7.5°/6.5°	
Side Shift	6.5"	
Height, mast lowered	108"	101"
Reach	Scissors Reach	
Hose Rupture System	Yes	
Seat Belt Interlock	Yes	
Overhead Guard (FOP/ROP)	Yes	
Support Arms	Yes	
Mounting System	Easy Hitch®/Easy I	Mount/Moffett Mount
Overall Width	100"	
Cargo Bay Width	63"	
Overall Length	106" w/o Forks (Regular	101" w/o Forks (4-Way)
Overhang	72"	
Length under Truck	30"	
Ground Clearance	12"	
Warranty	1 year	24/36 months



Special Options and Packages, available
* Weight, includes mast, forks, full size tires & fluids
Kubota® is a registered trademark of the Kubota Tractor Corp



Z1

	Features	Options
Load Capacity @ 24" load center	3,300 lb	
Engine - Diesel	Kubota®	
Horsepower	25 HP @2700 rpm	
Driven Wheels	1	3
Personnel Alert Package	No	Yes
Deluxe Seat and Steering Wheel	Yes	
Anti Stall Hydraulic Control	No	
Weather Shield	Yes	
Tool Box	No	Yes
Pre-Cleaner	No	Yes
Brakes	Yes (rear)	
Front Tires	16"x 6" (Solid)	15"x 4" (Solid) 23"x 8.5" (pneumatic) (3-wd)
Rear Tires	23" x 8.5" (pneumatic)	
Sealed Tires	No	
Speed	6 mph	
Gradeability	30%	
Turning Radius	75"	
Lift Height	86"	118"
Weight*	3,400 lb	3,550 lb.
Tilt Forward/Back	6°/5°	
Side Shift	8"	
Height, mast lowered	79"	94"
Reach	Reach Forks	
Hose Rupture System	Yes	
Fork Length	47"	39"
Seat Belt Interlock	Yes	
Overhead Guard (FOP)	Yes	
Wheel Arms	Retracting	Folding (3-wd**)
Mounting System	Easy Mount	
Overall Width	64"	
Cargo Bay Width	55"	
Overall Length	93.5" w/o Forks	
Overhang	50"	
Length under Truck	8"-30" (retracting)	
Ground Clearance	8"	
Warranty	1 year	24/36 months
Special Options and Packages, available Weight, includes mast, forks, full size tires & fluids		

^{**1-}wd has retracting option. 3-wd has folding option.

***Reach forks are 2.25"H x 6.75"W and come in various lengths.