

R A T E D L I F T I N G C A P A C I T I E S (L B S .)

CRANE MODEL: 6255S

ID NO.: MODEL 6255S

DATE: 10-25-2004

OVER THE REAR								
24 FEET BOOM			39 FEET BOOM			55 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	60800*						
8	72	51470*						
10	67	45270*	10	78	33470*			
12	61	38390*	12	74	30930*			
15	52	29920	15	70	27620	15	77	25860
18	42	24410	18	65	23600	18	74	21960
20	33	21680	20	61	21500	20	71	19920
			25	52	16440	25	66	16030
			30	42	13020	30	59	13260
			35	28	10590	35	53	11090
						40	45	9290
						45	37	7890
						50	25	6760
						54	3	5980

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 6255S

ID NO.: MODEL 6255S

DATE: 10-25-2004

OVER THE SIDE								
24 FEET BOOM			39 FEET BOOM			55 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	60800*						
8	72	51470*						
10	67	45270*	10	78	33470*			
12	61	38390*	12	74	30930*			
15	52	29920	15	70	27620	15	77	25860
18	42	24410	18	65	23600	18	74	21960
20	33	21680	20	61	21500	20	71	19920
			25	52	14700	25	65	15360
			30	41	10450	30	59	11060
			35	27	7820	35	52	8420
						40	45	6630
						45	36	5330
						50	25	4350
						54	3	3680

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED

QUIK MFG. COMPANY (Q M C)

RATED LIFTING CAPACITIES (L B S .)

CRANE MODEL: 6255S

ID NO.: MODEL 6255S

DATE: 10-25-2004

OVER THE FRONT								
24 FEET BOOM			39 FEET BOOM			55 FEET BOOM		
WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD	WORKING RADIUS	BOOM ANGLE	RATED LOAD
6	77	60800*						
8	72	51470*						
10	67	45270*	10	78	33470*			
12	61	38390*	12	74	30930*			
15	52	29920	15	70	27620	15	77	25860
18	42	24410	18	65	23600	18	74	21960
20	33	19710	20	61	19430	20	71	19910
			25	52	11710	25	65	12440
			30	41	7930	30	59	8600
			35	27	5670	35	52	6310
						40	45	4800
						45	36	3720
						50	25	2900
						54	2	2350

* MAXIMUM LOAD WITH STANDARD REEVING IS 30000 LB.

WIRE ROPE CAPACITY (LBS.)								
PARTS LINE	1	2	3	4	5	6	7	8
LINE PULL	7600	15200	22800	30400*	38000*	45600*	53200*	60800*

DO NOT EXCEED PARTS OF LINE RATINGS

NOTES
1. LOAD DOES NOT INCLUDE BLOCKS, SLINGS, AND ALL OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED 2. LOAD RATINGS ARE FOR ZERO DEGREE LIST 3. LOADS MUST BE FREELY SUSPENDED