BERCO

BOOO BACK OF CAB TAIL MOUNT TRAILER MOUNT

LOG AND PULP LOADERS



SERCO

8000



GENERAL SPECIFICATIONS

LIFT CAPACITY

• 8000 lbs @ 10' radius (less weight of attachment)

BOOM REACH

 20' fixed length boom standard. Fixed length and telescoping jib booms available to 27'.

ROTATION

Continuous on turntable bearing

STANDARD FEATURES MAIN AND SECONDARY BOOMS

 Made from high strength structural tubing reinforced at all stress points.

BOOM CYLINDERS

 Double acting with cast iron internal parts and chrome plated shafts. Main lift cylinder 6" x 36" x 3". Secondary boom cylinder 5" x 35-l/2" x 2-1/2".

BOOM PIVOT PINS

 2" diameter made from 100,000 psi yield strength steel shafting.

BEARINGS

Tapered roller bearings at boom pivot points.

SWING SYSTEM

 Hydraulic motor powered double planetary gear box driving external tooth turntable bearing.

STABILIZERS

 Telescoping A-frame type with double acting cylinders controlled from operator's seat.

HYDRAULIC SYSTEM

- Tandem gear pump providing 35 & 20 GPM at 1400 pump RPM.
- Stack type Gresen V-42 control valve located under seat for increased operator visibility and safety.
- 45 gallon A-frame mounted hydraulic reservoir with external return line filter and removable access cover. (55 gallon truck frame mount tank also available.)
- Serco designed and built continuous rotation manifold with cast iron center spool and oversize ports for trouble-free operation.
- Oversize main pressure and return lines with bent tube-type fittings to eliminate heat problems.

MISCELLANEOUS

- Rotating operator's platform with guard rail.
- Optional 2-lever control systems.
- Rear-mount loading unit configuration available with heavy-duty sub-frame and fold down stabilizers.
- Fold down joysticks.

TWO HARBORS MACHINE... STAYING IN TOUCH

When building a well-designed, quality loader backed with dependable factory/dealer service and parts availability, we haven't forgotten the vital link between us...WE STAY IN TOUCH!

We owe a great deal of our acceptance and growth to our ability to communicate -- to work closely and recognize the needs of the people who operate our equipment.

Over the years this mutual exchange of ideas has led to the development of a line of loaders designed to work in your kind of wood---Built right to deliver years of dependable service...Priced right with no sacrifice in quality and craftsmanship.

MODELS RANGING UP TO 37,000 LBS. LIFT CAPACITY

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE



611 2nd Ave. Two Harbors, MN 55616 (218)834-5118



PRINTED IN USA