

GR-XL Series

35-100 TON CAPACITY

**ROUGH
TERRAIN
CRANE**





GR-350XL

Crane capacity: 35 tons (31.8 metric tons)
4-section boom: 101.7 ft (31.0 m)
2-staged jib: 23.6 ft / 42 ft (7.2 m / 12.8 m)

GR-550XL

Crane capacity: 55 tons (50.0 metric tons)
4-section boom: 113.9 ft (34.7 m)
2-staged bi-fold jib: 28.9 ft / 50 ft (8.8 m / 15.2 m)

New Generation of Cranes



CONTENTS

NEW FEATURES

HELLO-NET System	03
The Environmentally Friendly Features	04
Fuel Monitoring System	05
Eco Mode System	
Positive Control System	

Crane

The Ultimate boom for rough terrain crane	07
Assist cylinder for jib	08
Jib installation	
Two winches with cable follower	
Two telescoping modes I & II	
New crane structure	
Bi-fold jib	09
Load moment indicator [AML-C]	11
Outrigger asymmetric extension width control	12
Operator comfort	13
Seat adjustment	14
Adjustment of control lever stand	
Wider steps and hand rails	

Carrier

New carrier frame	15
High performance engine	
Dashboard indicator and warning symbols	16
Smooth transmission	
Fastest travel speed	17
Comfortable suspension	
Axle	
Brake systems	
4 steering modes	
Self-removable counterweight	

WORKING RANGE & DIMENSION

SPECIFICATIONS

GR-750XL

Crane capacity: 75 tons (68.0 metric tons)
5-section boom: 141.1 ft (43.0 m)
2-staged bi-fold jib: 33.2 ft / 58.1 ft (10.1 m / 17.7 m)

GR-10000XL

Crane capacity: 100 tons (90.7 metric tons)
5-section boom: 154.2 ft (47.0 m)
2-staged bi-fold jib: 33.2 ft / 58.1 ft (10.1 m / 17.7 m)

At Tadano, crane development is our number one priority.
Our goal is to provide the safest, most innovative and reliable cranes in the industry that are able to handle all aspects of your job.
Tadano has a rough terrain crane solution for even the most hard to reach projects.
Our cranes adapt to the changing needs of your business and at the same time reduce environmental impact.
Experience the new generation of cranes!

NEW FEATURES

HELLO-NET System

TADANO supports your crane management via the Internet, providing information about operational status, position and maintenance.

HELLO-NET Owner's Site enables sharing of machine data between TADANO Group and machine owners. We offer you advanced customer support.



Monitoring machine information from your computer

1. Work History


HELLO-NET Owner's Site can display the day-to-day operational status, mileage and remaining fuel for each machine that is equipped with a communication terminal. In addition, you can view a list displaying the number of hours of operation and the mileage of all your machines for any specified month.

2. Machine Position Data

Using HELLO-NET Owner's Site, you can check a machine's latest position (up until previous day) on a map. Two types of position data, listed below, are transmitted automatically from your machine once every day. Work Site: The location where the machine's PTO has been activated (for one hour or more). Position at Day's End: The final location from which GPS was able to receive data on a given day.

3. Maintenance Information

You can check the maintenance timetable of your machines for periodical replacement parts and inspection schedule. HELLO-NET supports the maintenance of your machine.




HELLO-NET Telematics - Available in the U.S. and Canada, other countries may vary. Contact your distributor or sales@tadano-cranes.com for details.

The Environmentally Friendly Features

Designed to minimize environmental impact.



Fuel consumption indicator



TADANO's rough terrain cranes are equipped with Fuel Monitoring System, Eco Mode System and Positive Control Systems that substantially reduce fuel consumption and CO₂ emissions.



Introducing Fuel Monitoring System

The Fuel Monitoring System, displayed on the AML-C screen, monitors fuel consumption rates during crane operations, idling, and while traveling, allowing the operator to optimize fuel efficiency, reduce CO₂ emissions and noise level.



Two devices reduce fuel consumption


TADANO aims to reduce fuel consumption by its two newly developed technologies, the Eco Mode System and the Positive Control System. Consideration was given to the length of actual operating hours as well as non-operating time (when the crane is in a state of idling). In this relation, the average ratio between the operating hours and the non-operating time is 40/60% according to the results of our investigation. This understanding helped us to successfully achieve our objectives.



Eco Mode System - reduces fuel consumption by approximately 40% while the crane is being operated.



Positive Control System - reduces fuel consumption by approximately 60% when the crane is in a state of idling.




Fuel Monitoring System


The Fuel Monitoring System constantly monitors fuel consumption on the AML screen.

Checking this monitor enables you to prevent wasteful fuel consumption from unnecessary acceleration and idling.

Working




Driving



Eco Mode System

The Eco Mode System controls the maximum engine speed at the time of crane operation. To prevent an unnecessary rise in engine speed when there is excessive acceleration, the system enables fuel consumption and CO₂ emissions to decrease by Max. 22% with Eco mode I, and Max. 30% with Eco mode II, and the noise level is reduced.

Fuel consumption CO₂ emissions




Eco mode 1

Eco mode 2


* The above figures differ according to the type of crane used and its operating conditions.

Screen setting the eco mode to be selected



Eco mode switch


ECO mode indicator



Positive Control System

The Positive Control System effectively controls the quantity of hydraulic pump discharge during crane operation in response to the amount of movement applied by the operating control lever.

When the crane is in a state of idling, the Positive Control System keeps the quantity of hydraulic pump discharge to a minimum, reducing fuel consumption and CO₂ emissions by up to 20%.



* Comparison made when a crane is not being operated

* The above figures differ according to the type of crane used and its operating conditions.




Crane



New Design

The Ultimate boom for rough terrain crane (GR-1000XL, GR-750XL, GR-550XL)

The rounded boom is made of high tensile steel, which allows for decreased boom weight and increased boom strength. The high performance AML-C comes standard and aids the operator in maintaining a safe operation.



GR-350XL

The hexagonal boom



Assist cylinder for jib


(GR-1000XL, GR-750XL, GR-550XL)

When mounting and stowing the jib, the assist hydraulic cylinders are used resulting in increased work efficiency and safety.



Jib installation

(GR-1000XL, GR-750XL, GR-550XL)



Two winches with cable follower

Both the main winch and the auxiliary winch have powerful line pull and operate at high speeds thus enhancing work efficiency.

*Maximum permissible line pull may be affected by wire rope strength.



Photo : GR-750XL

Two telescoping modes I & II

(GR-1000XL, GR-750XL)

The operator has enhanced capabilities with two boom telescoping options whichever suits the lift needs.



Mode I

Mode I is extension of 2nd section only.

Then follows the synchronized extension of 3rd, 4th and 5th sections.



Mode II

Mode II is synchronized extension of 3rd, 4th and 5th sections.

Then 2nd section extends independently.

New crane structure (GR-1000XL, GR-750XL, GR-550XL)


During development of the structural shape of the crane,


*FEM analysis was applied to achieve a design tailored for optimal operation.

The slewing frames' structure ensures a highly rigid, compact style that is well suited for the overall planned design of the crane.

Continuing the TADANO tradition of excellence and innovation.

*FEM: Finite Element Method






Bi-fold jib


(GR-1000XL, GR-750XL, GR-550XL)

A two-stage, bi-fold lattice-type jib is used for this model of crane.


Crane capacity: 100 tons (90.7 metric tons)
 5-section boom: 154.2 ft (47.0 m)
 2-staged bi-fold jib: 33.2 ft / 58.1 ft (10.1 m / 17.7 m)
 Maximum lifting height: 154.5 ft (47.1 m) [Boom]
 211.3 ft (64.4 m) [Jib]
 Maximum load radius: 135.0 ft (41.2 m) [Boom]
 177.0 ft (53.9 m) [Jib]



GR-1000XL



Crane capacity: 75 tons (68.0 metric tons)
 5-section boom: 141.1 ft (43.0 m)
 2-staged bi-fold jib: 33.2 ft / 58.1 ft (10.1 m / 17.7 m)
 Maximum lifting height: 142.4 ft (43.4 m) [Boom]
 198.9 ft (60.5 m) [Jib]
 Maximum load radius: 132.5 ft (39.6 m) [Boom]
 165.0 ft (50.3 m) [Jib]



GR-750XL

220

200

180

160

140

120

100


80

60


40

20


0



Crane capacity: 55 tons (50.0 metric tons)
 4-section boom: 113.9 ft (34.7 m)
 2-staged bi-fold jib: 28.9 ft / 50 ft (8.8 m / 15.2 m)
 Maximum lifting height: 114.5 ft (34.9 m) [Boom]
 164.3 ft (50.1 m) [Jib]
 Maximum load radius: 105.4 ft (32.0 m) [Boom]
 138.5 ft (42.2 m) [Jib]




GR-550XL



Jib (GR-350XL)
 Box type top section telescopes
 from lattice type base section which
 stows alongside base boom section.

Crane capacity: 35 tons (31.8 metric tons)
 4-section boom: 101.7 ft (31.0 m)
 2-staged jib: 23.6 ft / 42 ft (7.2 m / 12.8 m)
 Maximum lifting height: 104.3 ft (31.8 m) [Boom]
 144.3 ft (44.0 m) [Jib]
 Maximum load radius: 93.6 ft (27.4 m) [Boom]
 122.0 ft (37.2 m) [Jib]




GR-350XL

Load moment indicator [AML-C]


Tadano's AML-C is easy to use, innovative in design, displays important information to the operator and enables the operator to preset a custom working environment. For example, the AML-C shows the boom angle, boom length, load radius, operating pressure of the elevating cylinder, the extension width of the outriggers, slewing position, rated lifting capacity and present hook load. These features allow the AML-C to move seamlessly through all lifting operations without having to change configurations or input new codes to make the lift. The AML-C safety features provide both audible and visual warnings. When an operation approaches the load limit Tadano's slow stop function engages to avoid shock loads.

Drum rotation indicator


To let the operator know when the winch is rotating, the drum rotation indicator on the AML beeps and flashes sequentially. The moving distance of the hook block per one flash of the indicator is approximately 7.9 in. to 11.8 in. (20 cm to 30 cm).



AML display symbols



AML lamp





Safety First!

Outrigger asymmetric extension width control

When operating the crane with the asymmetric outriggers extended, the AML-C detects the extension width of all of the Crane's outriggers (front, rear, left and right) to measure maximum work capacity in each area.

When slewing the boom from the longer outrigger area to the shorter outrigger area, the AML-C detects the motion and displays the maximum capacity according to the extension width of each of the outriggers, and brings the motion to a slow stop before it reaches the maximum capacity. Therefore, even in the case of operator error, the AML-C's slow stop function will help to minimize any safety risk.



Operator comfort

The crane cab provides improved livability and offers the operator a comfortable working environment.



Photo: GR-1000XL




Air conditioning and heating.

The control levers are smooth and responsive to the operators touch.




Seat adjustment

Multiple seat adjustment positions for ease of operation.



Adjustment of control lever stand

- The control lever stand has a 3-stage adjustment feature.
- Before you enter or exit the cab, or when you complete the crane operation, set the control lever stand on the left to the stowing position.
- The unlock lever is used by pulling to adjust for all positions of the control lever stand.



Wider steps and hand rails



Photo: GR-1000XL, GR-750XL

Front steps



Photo: GR-1000XL, GR-750XL

Rear steps



Photo: GR-1000XL, GR-750XL

Left side steps



Photo: GR-1000XL, GR-750XL

Right side steps




Photo: GR-1000XL

New carrier frame (GR-1000XL, GR-750XL, GR-550XL)

The new carrier frame design was developed and built so that its lightweight is compatible with its high rigidity to achieve an advanced level of performance. As a result, the rigidity was enhanced by as much as *35% which enables highly stabilized maneuverability for the new model of crane.

*Compared with our conventional crane models



High performance engine




Cummins QSB6.7 [Tier 4]

Model	Cummins QSB6.7 [Tier 4]
Type	4 cycle, turbo charged and after cooled, 6 cylinder in-line, direct injection, water cooled diesel engine.
Piston displacement	409 in ³ (6,700 cm ³)



Photo: GR-1000XL

Dashboard indicator and warning symbols



Smooth transmission

- Electronically controlled, fully automatic transmission.
- Torque converter with full power shift driving axle selector.
- 6 forward and 2 reverse speeds, constant mesh.

GR-1000XL, GR-750XL

3 speeds - High range - 2 wheel drive; 4 wheel drive
3 speeds - Low range - 4 wheel drive

GR-550XL

4 speeds - High range - 2 wheel drive; 4 wheel drive
4 speeds - Low range - 4 wheel drive

GR-350XL

4 speeds - High range - 2 wheel drive; 4 wheel drive
4 speeds - Low range - 4 wheel drive

Fastest traveling speed (GR-550XL, GR-350XL)

Maximum traveling speed 31 MPH (50 km/h)
Cummins Engine + 6 forward speeds transmission

Comfortable suspension (GR-550XL, GR-350XL)

Semi-elliptic leaf springs with hydraulic lockout device provide good riding comfort.



Axle

Front: Full floating type, steering and driving axle with planetary reduction.

Rear: Full floating type, steering and driving axle with planetary reduction and non-spin rear differential.

Brake systems

Service: Air over hydraulic disc brakes on all 4 wheels.

Parking/Emergency: Spring applied-air released brake acting on input shaft of front axle.

Auxiliary: Electropneumatic operated exhaust brake.

4 steering modes

Hydraulic power steering



			GR-1000XL	GR-750XL	GR-550XL	GR-350XL
Traveling on roads Driving in work site		2 wheel front Front steering only. This steering method is the same as that of general vehicles.	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
		2 wheel rear Rear steering only. The rear end of the vehicle swings outward like a forklift. Useful for easy approach of a narrow area.	<input type="radio"/>	<input type="radio"/>	—	—
Driving in work site		4 wheel coordinated Front and rear wheels are steered in opposite directions. The turning radius is decreased. Useful for movement in a small area.	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
		4 wheel crab Front and rear wheels are steered in the same direction. The vehicle can move diagonally. Useful for pulling over.	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Self-removable counterweight (GR-1000XL)

When using the auxiliary winch, dismantled counterweights can be lifted and moved for transport, and then remounted for operation at a work site without a helper crane.

Weight of removable counterweight: 22,000 lbs (9,979 kg)



GR-1000XL

Max. traveling speed: 22 mph (36 km/h)
 Overall length: approx. 47' 2" (14,375 mm)
 Overall width: approx. 10' 10-1/2" (3,315 mm)
 Overall height: approx. 12' 5-3/8" (3,795 mm)
 Min. turning radius (at center of extreme outer tire)
 2-wheel steering: 39' 1" (11.9 m)
 4-wheel steering: 22' 4" (6.8 m)



GR-750XL

Max. traveling speed: 22 mph (36 km/h)
 Overall length: approx. 43' 10-3/4" (13,380 mm)
 Overall width: approx. 10' 10-1/2" (3,315 mm)
 Overall height: approx. 12' 5-1/2" (3,790 mm)
 Min. turning radius (at center of extreme outer tire)
 2-wheel steering: 39' 1" (11.9 m)
 4-wheel steering: 22' 4" (6.8 m)



GR-550XL

Max. traveling speed: 31 mph (50 km/h)
 Overall length: approx. 42' 10" (13,055 mm)
 Overall width: approx. 9' 9-3/8" (2,980 mm)
 Overall height: approx. 12' 2-7/8" (3,730 mm)
 Min. turning radius (at center of extreme outer tire)
 2-wheel steering: 38' 5" (11.7 m)
 4-wheel steering: 22' (6.7 m)




GR-350XL

Max. traveling speed: 31 mph (50 km/h)
 Overall length: approx. 36' 10-3/4" (11,245 mm)
 Overall width: approx. 8' 10-1/2" (2,705 mm)
 Overall height: approx. 11' 5" (3,480 mm)
 Min. turning radius (at center of extreme outer tire)
 2-wheel steering: 37' 5" (11.4 m)
 4-wheel steering: 21' 4" (6.5 m)




GR-1000XL

WORKING RANGE




DIMENSIONS

Note: Dimension is with boom angle at -1.5 degree.
() Reference dimensions in mm.




GR-750XL

WORKING RANGE



DIMENSIONS

Note: Dimension is with boom angle at -1.6 degree.
() Reference dimensions in mm.



SPECIFICATIONS

MODEL	GR-1000XL	GR-750XL
MAXIMUM CAPACITY	200,000 lbs at 8 ft (90,720 kg at 2.44 m)	150,000 lbs at 8 ft (68,040 kg at 2.44 m)
TRAVELING SPEED(MAX.)	22 mph (36 km)	22 mph (36 km)
GRADEABILITY (TAN θ)	94 % (at stall) *Machine should be operated within the limit of engine crankcase design.	147 % (at stall) *Machine should be operated within the limit of engine crankcase design.
WEIGHT Gross vehicle mass -front axle -rear axle	115,610 lbs (52,440 kg) 57,340 lbs (26,010 kg) 58,270 lbs (26,430 kg)	97,620 lbs (44,280 kg) 49,650 lbs (22,520 kg) 47,970 lbs (21,760 kg)
MIN. TURNING RADIUS	2-wheel steering: 39' 1" (11.9 m), 4-wheel steering: 22' 4" (6.8 m) (at center of extreme outer tire)	2-wheel steering: 39' 1" (11.9 m), 4-wheel steering: 22' 4" (6.8 m) (at center of extreme outer tire)
BOOM Fully retracted length Fully extended length Extension speed Elevation speed	5-section full power synchronized telescoping boom 39.4' (12.0 m) 154.2' (47.0 m) 114.8' (35.0 m) in 160 seconds 20° to 60° in 46 seconds	5-section full power synchronized telescoping boom 36.1' (11.0 m) 141.1' (43.0 m) 105' (32.0 m) in 128 seconds 20° to 60° in 46 seconds
JIB Length	2-stage bi-fold lattice type jib. Triple offset (3.5' / 25' / 45') type. Assistant cylinders for mounting and stowing. 33.2' (10.1 m) or 58.1' (17.7 m)	2-stage bi-fold lattice type jib. Triple offset (3.5' / 25' / 45') type. Assistant cylinders for mounting and stowing. 33.2' (10.1 m) or 58.1' (17.7 m)
MAIN WINCH Maximum single line pull Single line speed Wire rope	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 20,000 lbs (9,090 kg) 491 FPM (149 m/min) (4th layer) 830' of 3/4" diameter rope (253 m of 19 mm)	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 15,200 lbs (6,880 kg) 446 FPM (136 m/min) (4th layer) 771' of 3/4" diameter rope (235 m of 19 mm)
AUXILIARY WINCH Maximum single line pull Single line speed Wire rope	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 20,000 lbs (9,090 kg) 491 FPM (149 m/min) (4th layer) 456' of 3/4" diameter rope (139 m of 19 mm)	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 15,200 lbs (6,880 kg) 446 FPM (136 m/min) (4th layer) 436' of 3/4" diameter rope (133 m of 19 mm)
SLEWING SPEED Tail slewing radius	1.5 min ⁻¹ {rpm} 13' 9" (4,190 mm)	2.4 min ⁻¹ {rpm} 13' 9" (4,190 mm)
HYDRAULIC SYSTEM	Pumps ... 2 variable piston pumps for crane functions. Tandem gear pump for steering, slewing and optional equipment. Control valves... Multiple valves actuated by pilot pressure with integral pressure relief valves. Circuit ... Equipped with air cooled type oil cooler. Oil pressure appears on AML display for main circuit. Hydraulic oil tank capacity... approx. 202 gallon (763 liters)	Pumps ... 2 variable piston pumps for crane functions. Tandem gear pump for steering, slewing and optional equipment. Control valves... Multiple valves actuated by pilot pressure with integral pressure relief valves. Circuit ... Equipped with air cooled type oil cooler. Oil pressure appears on AML display for main circuit. Hydraulic oil tank capacity... approx. 202 gallon (763 liters)
LOAD MOMENT INDICATOR (TADANO AML-C)	Main unit in crane cab gives audible and visual warning of approach to overload. The AML monitors each outrigger extended length and automatically programs the corresponding "RATED LIFTING CAPACITIES" table. It also has the limit function of working range (load radius / boom angle / tip height / slewing range). Automatic speed reduction and slow stop function for boom elevation and / or slewing. Following information is displayed: ·Moment load in percentage ·Permissible load ·Actual hook load ·Boom length ·Boom angle ·Load radius ·Jib length ·Jib offset angle ·Potential lifting height ·Slewing angle ·Number of parts of line ·Boom position indicator ·Outtrigger position or on-rubber indicator ·Main hydraulic pressure ·Fuel consumption monitor The AML-C including Tare function and Drum rotation indicator.	Main unit in crane cab gives audible and visual warning of approach to overload. The AML monitors each outrigger extended length and automatically programs the corresponding "RATED LIFTING CAPACITIES" table. It also has the limit function of working range (load radius / boom angle / tip height / slewing range). Automatic speed reduction and slow stop function for boom elevation and / or slewing. Following information is displayed: ·Moment load in percentage ·Permissible load ·Actual hook load ·Boom length ·Boom angle ·Load radius ·Jib length ·Jib offset angle ·Potential lifting height ·Slewing angle ·Number of parts of line ·Boom position indicator ·Outtrigger position or on-rubber indicator ·Main hydraulic pressure ·Fuel consumption monitor The AML-C including Tare function and Drum rotation indicator.
OUTRIGGERS Extension width	4-hydraulically operated H-type outriggers. Each outrigger controlled simultaneously or independently from the cab. Equipped with extension width detector for each outrigger. Max... 23' 11-3/8" (7.3 m), Mid... 21' 11-3/4" (6.7 m) & 18' 1/2" (5.5 m), Min ... 8' 10-5/16" (2.7 m), Float size (Diameter) ...1' 11-5/8" (0.6 m)	4-hydraulically operated H-type outriggers. Each outrigger controlled simultaneously or independently from the cab. Equipped with extension width detector for each outrigger. Max... 23' 11-3/8" (7.3 m), Mid... 21' 11-3/4" (6.7 m) & 18' 1/2" (5.5 m), Min ... 8' 10-5/16" (2.7 m), Float size (Diameter) ...1' 11-5/8" (0.6 m)
CARRIER	Rear engine, left hand steering, driving axle 2-way selected type (by manual switch). 4 x 2 front drive, 4 x 4 front and rear drive.	Rear engine, left hand steering, driving axle 2-way selected type (by manual switch). 4 x 2 front drive, 4 x 4 front and rear drive.
ENGINE	4 cycle, turbo charged and after cooled, 6 cylinder in-line, direct injection, water cooled diesel engine.	4 cycle, turbo charged and after cooled, 6 cylinder in-line, direct injection, water cooled diesel engine.
TRANSMISSION	Electronically controlled fully automatic transmission.	Electronically controlled fully automatic transmission.
STEERING	Hydraulic power steering. 4 steering modes available: 2-wheel front, 2-wheel rear, 4-wheel coordinated, 4-wheel crab	Hydraulic power steering. 4 steering modes available: 2-wheel front, 2-wheel rear, 4-wheel coordinated, 4-wheel crab
SUSPENSION	Front..... Rigid mounted to the frame. Rear..... Pivot mounted with hydraulic lockout device.	Front..... Rigid mounted to the frame. Rear..... Pivot mounted with hydraulic lockout device.
TIRES	29.5 - 25 34PR(OR)	29.5 - 25 22PR(OR) or 29.5 - 25 28PR(OR)
FUEL TANK CAPACITY	79.2 gallon (300 liters)	79.2 gallon (300 liters)

MODEL	GR-550XL	GR-350XL
MAXIMUM CAPACITY	110,000 lbs at 8 ft (50,000 kg at 2.44 m)	70,000 lbs at 8 ft (31,752 kg at 2.44 m)
TRAVELING SPEED(MAX.)	31 mph (50 km)	31 mph (50 km)
GRADEABILITY (TAN θ)	69 % (at stall) *Machine should be operated within the limit of engine crankcase design.	78 % (at stall) *Machine should be operated within the limit of engine crankcase design.
WEIGHT Gross vehicle mass -front axle -rear axle	74,850 lbs (33,950 kg) 38,500 lbs (17,460 kg) 36,350 lbs (16,490 kg)	60,830 lbs (27,590 kg) 30,380 lbs (13,780 kg) 30,450 lbs (13,810 kg)
MIN. TURNING RADIUS	2-wheel steering: 38' 5" (11.7 m), 4-wheel steering: 22' (6.7 m) (at center of extreme outer tire)	2-wheel steering: 37' 5" (11.4 m), 4-wheel steering: 21' 4" (6.5 m) (at center of extreme outer tire)
BOOM Fully retracted length Fully extended length Extension speed Elevation speed	4-section full length power telescoping boom 35.1' (10.7 m) 113.9' (34.7 m) 78.8' (24.0 m) in 72 seconds 20° to 60° in 27 seconds	4-section full length power telescoping boom 31.8' (9.7 m) 101.7' (31.0 m) 69.9' (21.3m) in 91 seconds 20° to 60° in 22 seconds
JIB Length	2-staged swingaround boom extension. Triple offset (5' 25' 45') type. Assistant cylinders for mounting and stowing. 28.9' (8.8 m) or 50' (15.2 m)	2-staged swingaround boom extension. Triple offset (5' 25' 45') type. 23.6' (7.2 m) or 42' (12.8 m)
MAIN WINCH Maximum single line pull Single line speed Wire rope	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 15,200 lbs (6,880kg) 446 FPM (136 m/min) (4th layer) 633' of 3/4" diameter rope (193 m of 19 mm)	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 12,600 lbs (5,710 kg) 410 FPM (125 m/min) (4th layer) 558' of 5/8" diameter rope (170 m of 16 mm)
AUXILIARY WINCH Maximum single line pull Single line speed Wire rope	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 15,200 lbs (6,880 kg) 446 FPM (136 m/min) (4th layer) 361' of 3/4" diameter rope (110 m of 19 mm)	Variable speed type with grooved drum driven by hydraulic axial piston motor 1st layer 12,600 lbs (5,710 kg) 410 FPM (125 m/min) (4th layer) 322' of 5/8" diameter rope (98 m of 16 mm) * AUXILIARY WINCH (OPTIONAL)
SLEWING SPEED Tail slewing radius	2.7 min ⁻¹ {rpm} 13' 7" (4,140mm)	3.2 min ⁻¹ {rpm} 10' 11 - 1/8" (3,330mm)
HYDRAULIC SYSTEM	Pumps ... 2 variable piston pumps for crane functions. Tandem gear pump for steering, slewing and optional equipment. Control valves... Multiple valves actuated by pilot pressure with integral pressure relief valves. Circuit ... Equipped with air cooled type oil cooler. Oil pressure appears on AML display for main circuit. Hydraulic oil tank capacity... approx. 148 gallon (560 liters)	Pumps ... 2 variable piston pumps for crane functions. Tandem gear pump for steering, slewing and optional equipment. Control valves... Multiple valves actuated by pilot pressure with integral pressure relief valves. Circuit ... Equipped with air cooled type oil cooler. Oil pressure appears on AML display for main circuit. Hydraulic oil tank capacity... approx. 100 gallon (380 liters)
LOAD MOMENT INDICATOR (TADANO AML-C)	Main unit in crane cab gives audible and visual warning of approach to overload. The AML monitors each outrigger extended length and automatically programs the corresponding "RATED LIFTING CAPACITIES" table. It also has the limit function of working range (load radius / boom angle / tip height / slewing range). Automatic speed reduction and slow stop function for boom elevation and / or slewing. Following information is displayed: ·Moment load in percentage ·Permissible load ·Actual hook load ·Boom length ·Boom angle ·Load radius ·Jib length ·Jib offset angle ·Potential lifting height ·Slewing angle ·Number of parts of line ·Boom position indicator ·Outtrigger position or on-rubber indicator ·Main hydraulic pressure ·Fuel consumption monitor The AML-C including Tare function and Drum rotation indicator.	Main unit in crane cab gives audible and visual warning of approach to overload. The AML monitors each outrigger extended length and automatically programs the corresponding "RATED LIFTING CAPACITIES" table. It also has the limit function of working range (load radius / boom angle / tip height / slewing range). Automatic speed reduction and slow stop function for boom elevation and / or slewing. Following information is displayed: ·Moment load in percentage ·Permissible load ·Actual hook load ·Boom length ·Boom angle ·Load radius ·Jib length ·Jib offset angle ·Potential lifting height ·Slewing angle ·Number of parts of line ·Boom position indicator ·Outtrigger position or on-rubber indicator ·Main hydraulic pressure ·Fuel consumption monitor The AML-C including Tare function and Drum rotation indicator.
OUTRIGGERS Extension width	4-hydraulically operated H-type outriggers. Each outrigger controlled simultaneously or independently from the cab. Equipped with extension width detector for each outrigger. Max... 22'11 - 5/8" (7.0 m), Mid... 21'3 - 7/8" (6.5 m) & 16'4 - 7/8" (5.0 m), Min ... 8'1 - 5/8" (2.48 m), Float size (Diameter) ...1'7 - 11/16" (0.5 m)	4-hydraulically operated H-type outriggers. Each outrigger controlled simultaneously or independently from the cab. Equipped with extension width detector for each outrigger. Max... 20'8 (6.3 m), Mid... 19'4 - 1/4" (5.9 m) & 16'4 - 7/8" (5.0 m), Min ... 7'2 - 5/8" (2.2 m), Float size (Diameter) ...1'3 - 3/4" (0.4 m)
CARRIER	Rear engine, left hand steering, driving axle 2-way selected type (by manual switch). 4 x 2 front drive, 4 x 4 front and rear drive.	Rear engine, left hand steering, driving axle 2-way selected type (by manual switch). 4 x 2 front drive, 4 x 4 front and rear drive.
ENGINE	4 cycle, turbo charged and after cooled, 6 cylinder in-line, direct injection, water cooled diesel engine.	4 cycle, turbo charged and after cooled, 6 cylinder in-line, direct injection, water cooled diesel engine.
TRANSMISSION	Electronically controlled fully automatic transmission.	Electronically controlled fully automatic transmission.
STEERING	Hydraulic power steering. 3 steering modes available: 2-wheel front, 4-wheel coordinated, 4-wheel crab	Hydraulic power steering. Three steering modes available: 2-wheel front, 4-wheel coordinated, 4-wheel crab
SUSPENSION	Semi-elliptic leaf springs with hydraulic lockout device.	Semi-elliptic leaf springs with hydraulic lockout device.
TIRES	23.5 - 25(OR)	20.5 - 25(OR)
FUEL TANK CAPACITY	79.2 gallon (300 liters)	79.2 gallon (300 liters)

*Some specifications are subject to change without prior notification.



GR-1000XL (100 TON)



GR-750XL (75 TON)



GR-550XL (55 TON)



GR-350XL (35 TON)



TADANO AMERICA Corporation

4242 West Greens Road, Houston, TX 77066

Tel: 281-869-0030 Fax: 281-869-0040

www.tadanoamerica.com Email: sales@tadano-cranes.com

Parts Hotline: 713-865-1041 Service Hotline: 281-869-5925