


Construction Otility Trailers

Utility Trailers... Small Trailers With Big Capabilites



Adjustable Hitch

To accommodate a wide variety of towing vehicles, Trail King utility trailers come with an adjustable 4-bolt hitch, available in ball hitch or pintle hitch configuration (depending upon model).



Circuit Breaker

Each electrical function has its own circuit breaker, and each axle is fused separately, for increased safety of operation, less maintenance, and easier troubleshooting.



Safety Headboard

The 4" safety headboard provides an extra dimension of safety and load-hauling security.



Oak Deck

Trail King utility trailers are decked with 1½" nominal oak decking, not pine, and double screwed to crossmembers to prevent cupping. As a result, your deck will stand up to years of rugged service.



Lightweight Ramps

Standard self-supporting 60" laddertype ramps (inset photo) are lightweight, but strong. Also available in optional wood-filled and spring assist models.









Bolt-on Safety Chains

Heavy-duty safety chains are bolted on, rather than welded, so that their strength and performance are not compromised in any way.



Toolboxes

Two (2) toolboxes are conveniently located at the front of the trailer and are roomy enough to store all your chains and tools.



Tie-down Brackets

Trail King includes four (4) heavy-duty tie-down brackets as standard equipment... so you can securely transport even your toughest loads.



I-Beam Crossmembers

Full-width steel I-beam crossmembers provide load-bearing strength across the entire width of the trailer. And, to resist corrosion, the trailer is painted before the decking is added.



Axles, Tires, Fender

Torflex axies, radial tires, and a new, rounded fender... all standard equipment... deliver a smooth ride, long service life, and attractive appearance.



Protected Electrical System

Trail King utility trailers feature rubbermounted, shock-proof, sealed lights and rubber grommets wherever wiring runs through the frame... for longer, troublefree, low-maintenance performance life.

Construction Utility Trailers



STANDARD EQUIPMENT	MODELS				
	TK6U	TK8U	TK10	TK12	TK18
Payload capacity	6,000	8,000	10,000	12,000	18,000
Electric brakes on all axles					
Single disc wheel (6-hole)					
Single disc wheel (8-hole)					
ST205/75R x 15-6PR radial tires					
7.00 x 15-8PR radial tires					
ST225/75R x 15-8PR radial tires					
235/85R x 16 radial tires					
1½" oak decking (NET)					
Structural channel main frame					
Four (4) tie-down brackets					
Deck width between fenders	76"	76"	761/4"	84"	84"
Overall width	95"	95½"	95½"	102"	102"
Deck length	12'	14'	16'	16'	20'*
Loaded deck height	181/2"	19¾"	191/4"	21¾"	223/4"
Torflex axles	2 - 3,000-lb.	2 - 4,000-lb.	2 - 5,000-lb.	2 - 6,000-lb.	3 - 6,000-lb.
5' self-supporting loading ramps (18" wide)					
2,000-lb. Swivel jack					
5,000-lb. Jack stand					
H.D. enclosed fenders					
2 5/16" ball hitch, adjustable range:	161/4"-23"	17¾"-24½"	171/4"-24"	Not available	Not available
4-bolt pintle hitch, adjustable range:	Option	Option	Option	19"-25¾"	18¾"-30"
Electrical system per DOT regulations					
Safety chains (less hooks)					
Headboard					
Breakaway switch (less battery)					
Red & white conspicuity markings					
Color: Trail King off-white 2-part polyurethane					

*18 flatbed, 2 beavertail

All specifications are subject to change without notice. Trailers pictured in this brochure may feature optional equipment.

Distributed by:



TRAIL KING Industries Juction