

Telescopic Boom Lift

UpRight
POWERED ACCESS




- ☐ 22.1m max. working height
- ☐ 17.1m max. outreach
- ☐ 1.8m, 90° jib
- ☐ 180° hydraulic powered platform rotation
- ☐ Driveable at full height
- ☐ Proportional control of drive, boom lift and slew
- ☐ 4 wheel drive

**SB66
JRT**

SB66JRT boom lift specifications

SB66JRT	
max. working height	22.1m
max. platform height	20.1m
max. outreach	17.1m
platform capacity (SWL)	227kg
platform size	0.76m x 1.52m
platform rotation	180°
jib length	1.8m
jib working arc	90°
overall width	2.5m
operational width	2.5m
overall length A	10.1m
lowered height B	2.7m
min. transport length	10.1m
gross weight	11,340kg
inside turning radius	4.7m
max. drive speed (lowered)	4.8kmh
ground clearance	330mm
gradeability	65%
tyres	15 x 19.5 loader lug poly filled
drive system	4 wheel drive
controls	joystick proportional drive, lift and slew/ rheostat other boom functions
power source	Deutz F4L-2011 air cooled diesel 64hp

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate UpRight operators manual for detailed instructions on the proper use and maintenance.



BP1: SB66JRT 8/07

UpRight
POWERED ACCESS

Vigo Centre, Birtley Road, Washington,
Tyne & Wear, NE38 9DA, U.K.

Sales Tel: +44 (0) 845 1550 057 • Spare Parts Tel: +44 (0) 845 1550 058


www.upright.com

standard features

- 1.8m, 90° jib
- 180° hydraulic powered platform rotation
- 4 wheel drive
- Proportional control of drive, boom lift and slew
- Foam filled lug tyres
- Driveable at full height
- Operator horn
- Extra finger protection handrail
- 1 year parts and labour warranty
- 5 year structural warranty

options

- Hydraulic generator
- Bumpguard system
- Platform control box cover
- Twin platform work lights
- Airline to platform
- Amber beacon on boom
- Swing gate in lieu of drop bar
- Sand blast protection kit
- Driving lights
- Cold weather start kit
- Drive motion alarm
- Towing package
- 2.44m x 0.76m aluminium platform 227kg SWL



This product is available with the CE mark confirming compliance with all relevant European Machinery Directives

manufactured by

UpRight
POWERED ACCESS