

SHENYANG ZHENGCHUANG CONSTRUCTION MACHINERY CO., LTD  
SYM TOWER CRANE SPARE PARTS CO., LTD



Courtesy of [CranesMarket.com](http://CranesMarket.com)


# 载荷特性 Load diagrams

# ZCJJ<sup>®</sup>

JIB	Max. load	Jib Reach															
		t	s	15	20	25	30	35	40	45	50	55	60	65	70	75	80
80m		6.00	30.9	6.00	6.00	6.00	6.00	6.00	4.43	3.84	3.37	2.99	2.67	2.40	2.17	1.97	1.80
		12.00	16.7	12.00	9.77	7.50	6.02	4.97	4.19	3.58	3.10	2.71	2.39	2.11	1.88	1.68	1.50
75m		6.00	37.5	6.00	6.00	6.00	6.00	6.00	5.57	4.86	4.29	3.83	3.44	3.12	2.84	2.60	
		12.00	19.8	12.00	11.91	9.22	7.45	6.21	5.28	4.56	3.99	3.53	3.14	2.82	2.54	2.30	
70m		6.00	42.0	6.00	6.00	6.00	6.00	6.00	6.00	5.55	4.92	4.40	3.97	3.61	3.30		
		12.00	21.9	12.00	12.00	10.35	8.41	7.04	6.02	5.23	4.60	4.09	3.66	3.31	3.00		
65m		6.00	45.7	6.00	6.00	6.00	6.00	6.00	6.00	5.80	5.15	4.62	4.17	3.80			
		12.00	23.0	12.00	12.00	10.97	8.93	7.50	6.43	5.61	4.95	4.42	3.97	3.60			
60m		6.00	47.4	6.00	6.00	6.00	6.00	6.00	6.00	6.00	5.65	5.08	4.60				
		12.00	24.7	12.00	12.00	11.87	9.70	8.16	7.03	6.15	5.44	4.87	4.40				
50m		6.00	56.0	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00					
		12.00	26.1	12.00	12.00	12.00	10.30	8.86	7.47	6.54	5.80						
40m		6.00	40.0	6.00	6.00	6.00	6.00	6.00	6.00								
		12.00	27.8	12.00	12.00	12.00	10.94	9.25	8.00								

## 附着 Anchorages

2.0m × 2.0m




Courtesy of CraneMarket.com

# 塔身截面 Mast


2.0m X 2.0m

TCT8018-12



F 反力 Reactions	<ul style="list-style-type: none"> <li>工作状态 in service</li> <li>非工作状态 Out of service</li> </ul>	⊕ 自重 Self-load 不带载荷及配重最大臂长及标准高度时的自重 Without load and ballast With longest jib and Free standing height
----------------	---	--








# 爬升 Climbing crane



塔身 Tower	L6802	
	塔身高度 Tower height	塔身重量 Tower weight
1	2.0	1.1
2	2.2	
3	—	24.5 22.8
4	—	111 98.0
5	14.8	
6	20.1	

Courtesy of CraneMarket.com

# 机构性能 Mechanisms Specification

机构性能 Mechanisms specification								电机 (kw) Motor
			m/min	t	m/min	t		
起升 Hoisting		SSLVF	0-45	6.0	0-22.5	12	500m	55
			0-90	3.0	0-45	6.0		
变幅 Trolleying		6JDF	0-65				500m	5.5
回转 Slewing		RCV95	0.67					
行走 Travelling		4TRVF	12					
电源 Mains supply					380V/50HZ 440V/60HZ			
供电容量 Necessary electric power					85 KVA			

以上参数可按用户要求配置

The related parameters could be configured according to clients requests

执行标准

Voluntary Standards: GB/T13752

## 运输 Shipping

塔身 Tower	高度 (m) Ht (m)	集装箱数量 Container Qty			
		FR	40' GP	40' HQ	20' GP
L6882	52.0			9	

Office Address: Gate 1, No 256 Dongbei  
damalu, Dadong district, Shenyang, China  
Factory Address: Shenbei Industrial  
development zone, Shenyang City, Liaoning  
Province, China.  
Postcode: 110044  
Tel: 0086-24-88901098  
Fax: 0086-24-88905922  
Website: www.towercranesupply.com

Freign Trade Manager:  
Donovan Zhang  
What App: +8615702499847  
Email: Sales3@cn-zcjj.com  
Twitter: @ZCJJ\_donovan

**ZCJJ**  
正创建机

Courtesy of CraneMarket.com